



DESCRIPTION:

SWL supports have an integrated lid for securing sections of corrugated conduits between various parts of the electrical installation on machines. Ideal for securing conduit in situations e.g. on ceilings.

SPECIFICATION:

MATERIAL: Polyamide (PA 6) - Free of Halogen, Phosphorus and Cadmium. Self-Extinguishing, Shock Resistant

IP RATING: IP 66 Protection. IP68 with ORJ O-Rings

SERVICE TEMPERATURE RANGE: -40°C to +105°C

STANDARDS: EN 60204 (Safety of Machinery).



PART NUMBERS:

PART NO. BLACK	PART NO. GREY	CONDUIT SIZE (mm)	DIMENSIONS (mm)					PACK QTY
			A	B	C	H	M (Bolt)	
SWL-12B	SWL-12G	12	25	22	20	13	M5	10
SWL-16B	SWL-16G	16	27	25	20	15	M5	10
SWL-20B	SWL-20G	20	33	31	20	19	M5	10
SWL-25B	SWL-25G	25	42	40	20	23	M6	10
SWL-32B	SWL-32G	32	47	46	20	26	M6	10
SWL-40B	SWL-40G	40	56	56	20	31	M6	10
SWL-50B	SWL-50G	50	70	70	20	39	M6	10



CABLECRAFT
creative wiring solutions



Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.
Phone: 01582 606033 • Fax: 01582 606063 • Email: sales@cablecraft.co.uk • Web: www.cablecraft.co.uk

VAT NO. GB 639 920 900 • CO. REG. NO. 2478297