



| PART No | A | B | C | D | øE | F |
|----------|------|------|-----|------|------|-----|
| PCLIP/10 | 13.5 | 12.7 | 3.5 | 9.5 | 5.2 | 1.4 |
| PCLIP/12 | 15.3 | 12.7 | 3.5 | 14.0 | 5.2 | 1.4 |
| PCLIP/16 | 17.3 | 12.7 | 3.5 | 17.0 | 5.2 | 1.4 |
| PCLIP/20 | 19.3 | 12.7 | 3.5 | 21.0 | 5.2 | 1.4 |
| PCLIP/25 | 21.5 | 12.7 | 3.5 | 25.5 | 5.2 | 1.4 |
| PCLIP/32 | 25.8 | 12.7 | 3.5 | 34.0 | 5.2 | 1.4 |
| PCLIP/40 | 37.3 | 19.1 | 4.5 | 44.5 | 10.2 | 2.4 |
| PCLIP/50 | 43.5 | 25.4 | 4.5 | 57.2 | 14.2 | 2.4 |
| PCLIP/63 | 46.8 | 25.4 | 4.5 | 63.5 | 14.2 | 2.4 |
| PCLIP/75 | 55.0 | 25.4 | 4.5 | 76.2 | 14.2 | 2.4 |
| | | | | | | |

MATERIAL: MILD STEEL TO BS EN 1030 FEPO
 FINISH: BRIGHT ZINC PLATE TO BS1706 Fe/ZN5c 1A
 LINER: PVC BLACK TO BS2571
 TEMPERATURE RANGE -25°C TO +105°C



BIRMINGHAM ENGLAND

This drawing/document is a COPYRIGHT and the property ADAPTAFLEX LIMITED It must not be copied (in whole or part) used for manufacture or otherwise disclosed without prior written consent of the company. The Company's policy is one of continuous improvement and it therefore reserves the right to change specifications at any time without notice.

MATERIAL **SEE ABOVE**

SLEEVE **SEE ABOVE**

COLOUR **STEEL/BLACK**

DATE **08/02/06**

CHARTS 099

TITLE

**P/CLIP
 DATA SHEET**