

PAFS16/BL/50M



Products → Low Voltage Products and Systems → Installation Products
→ Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

General Information

Extended Product Type:	PAFS16/BL/50M
Product ID:	7TCA296000R2176
EAN:	5020963000317
Catalog Description:	STD WGT BLK NYL COND NC16 50M
Long Description:	Standard Weight Conduit, Nominal Conduit Size 16mm, NW Conduit Size 13, Fine Conduit Pitch, Outside Diameter 15.8mm, Inside Diameter 11.8mm, Static Bend Radius 35mm, Reel Length 50 Meters, Polyamide (Nylon) 6, Black

Ordering

EAN:	5020963000317
Minimum Order Quantity:	1 piece
Customs Tariff Number:	3926909996

Dimensions

Product Net Weight:	1.937 kg
----------------------------	----------

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	431.8 mm
Package Level 1 Height:	152.4 mm
Package Level 1 Depth / Length:	431.8 mm
Package Level 2 Units:	1 piece
Package Level 2 Width:	431.8 mm
Package Level 2 Height:	152.4 mm
Package Level 2 Depth / Length:	431.8 mm

Additional Information

Brand / Label:	Adaptaflex
Color:	Black
Function:	Indoors / Outdoors - Light Industrial, Buildings & Machinery
Material:	Polyamide/Nylon 6
Product Main Type:	ADAPTAFLEX FLEXIBLE CABLE PROTECTION
Product Name:	ADAPTAFLEX
Product Type:	Standard Weight Conduit with Fine Pitch

Special Functions:

High Fatigue Life, Self Extinguishing, Halogen Free

Certificates and Declarations (Document Number)

Data Sheet, Technical Information: PAFS16/BL/50M

Instructions and Manuals: PAFS16/BL/50M

Classifications

ETIM 6: EC001175 - Corrugated plastic hose

UNSPSC: 39131706

