

PAFS34/BL/25M



Products → Low Voltage Products and Systems → Installation Products
→ Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

General Information

| | |
|-------------------------------|---|
| Extended Product Type: | PAFS34/BL/25M |
| Product ID: | 7TCA296000R2248 |
| EAN: | 5020963001260 |
| Catalog Description: | STD WGT BLK FINE NYL COND NC34 25M |
| Long Description: | Standard Weight Conduit, Nominal Conduit Size 34mm, NW Conduit Size 29, Fine Conduit Pitch, Outside Diameter 34.5mm, Inside Diameter 28.8mm, Static Bend Radius 60mm, Reel Length 25 Meters, Polyamide (Nylon) 6, Black |

Ordering

| | |
|--------------------------------|---------------|
| EAN: | 5020963001260 |
| Minimum Order Quantity: | 1 piece |
| Customs Tariff Number: | 3926909990 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Weight: | 3.375 kg |
|----------------------------|----------|

Container Information

| | |
|--|----------|
| Package Level 1 Units: | 1 piece |
| Package Level 1 Width: | 939.8 mm |
| Package Level 1 Height: | 431.8 mm |
| Package Level 1 Depth / Length: | 431.8 mm |
| Package Level 2 Units: | 1 piece |
| Package Level 2 Width: | 939.8 mm |
| Package Level 2 Height: | 431.8 mm |
| Package Level 2 Depth / Length: | 431.8 mm |

Additional Information

| | |
|---------------------------|--|
| Brand / Label: | Adaptaflex |
| Color: | Black |
| Function: | Indoors / Outdoors - Light Industrial, Buildings & Machinery |
| Material: | Polyamide/Nylon 6 |
| Product Main Type: | ADAPTAFLEX FLEXIBLE CABLE PROTECTION |
| Product Name: | "flexible conduit, nylon" |
| Product Type: | Standard Weight Conduit with Fine Pitch |

Special Functions: High Fatigue Life, Self Extinguishing, Halogen Free

UPC: 786210147154

Certificates and Declarations (Document Number)

Data Sheet, Technical Information: PAFS34/BL/25M

Instructions and Manuals: PAFS34/BL/25M

Classifications

ETIM 6: EC001175 - Corrugated plastic hose

UNSPSC: 39131706

