

PAFS16/BL/25M



Products → Low Voltage Products and Systems → Installation Products
→ Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

General Information

Extended Product Type:	PAFS16/BL/25M
Product ID:	7TCA296000R2173
EAN:	5020963002533
Catalog Description:	STD WGT BLK NYL COND NC16 25M
Long Description:	Standard Weight Conduit, Nominal Conduit Size 16mm, NW Conduit Size 13, Fine Conduit Pitch, Outside Diameter 15.8mm, Inside Diameter 11.8mm, Static Bend Radius 35mm, Reel Length 25 Meters, Polyamide (Nylon) 6, Black

Ordering

EAN:	5020963002533
Minimum Order Quantity:	1 piece
Customs Tariff Number:	3926909990

Dimensions

Product Net Weight:	6.418 kg
----------------------------	----------

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	939.8 mm
Package Level 1 Height:	431.8 mm
Package Level 1 Depth / Length:	431.8 mm
Package Level 2 Units:	1 piece
Package Level 2 Width:	939.8 mm
Package Level 2 Height:	431.8 mm
Package Level 2 Depth / Length:	431.8 mm

Additional Information

Brand / Label:	Adaptaflex
Color:	Black
Function:	Indoors / Outdoors - Light Industrial, Buildings & Machinery
Material:	Polyamide/Nylon 6
Product Main Type:	ADAPTAFLEX FLEXIBLE CABLE PROTECTION
Product Name:	"flexible conduit, nylon"
Product Type:	Standard Weight Conduit with Fine Pitch

Special Functions:

High Fatigue Life, Self Extinguishing, Halogen Free

Certificates and Declarations (Document Number)

Data Sheet, Technical Information: PAFS16/BL/25M

Instructions and Manuals: PAFS16/BL/25M

Classifications

ETIM 6: EC001175 - Corrugated plastic hose

UNSPSC: 39131706

