



DESCRIPTION:

Ideal for fixing the ends of flexible corrugated conduits to the cable entries on control panels, terminal boxes, electric motors etc. They are notable for their high tensile strength and tightness. Self-extinguishing, shock-resistant.

SPECIFICATION:

MATERIAL: Polyamide (PA 6) - Free of Halogen, Phosphorus and Cadmium.

IP RATING: IP 66 Protection. IP68 with ORJ O-Rings

SERVICE TEMPERATURE RANGE: -40°C to +105°C

STANDARDS: EN 60204 (Safety of Machinery).



PART NUMBERS:

PART NO. BLACK	PART NO. GREY	CONDUIT SIZE (mm)	THREAD SIZE	INT. DIA. (mm)	DIMENSIONS (mm)						PK QTY
					A	B	C	D	H	LR	
NEC-12M16B	NEC-12M16G	12	M16x1.5	10.0	35	42	21	21	11	11	1
NEC-16M16B	NEC-16M16G	16	M16x1.5	10.5	39	44	25	23	15	11	1
NEC-20M20B	NEC-20M20G	20	M20x1.5	14.5	45	58	30	30	18	11	1
NEC-25M25B	NEC-25M25G	25	M25x1.5	18.5	53	66	36	37	23	12	1
NEC-32M32B	NEC-32M32G	32	M32x1.5	25.5	66	76	45	46	27	15	1
NEC-40M40B	NEC-40M40G	40	M40x1.5	32.0	79	89	54	55	33	19	1
NEC-50M50B	NEC-50M50G	50	M50x1.5	42.0	92	103	68	69	39	19	1



CABLECRAFT
creative wiring solutions



Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.
Phone: 01582 606033 • Fax: 01582 606063 • Email: sales@cablecraft.co.uk • Web: www.cablecraft.co.uk

VAT NO. GB 639 920 900 • CO. REG. NO. 2478297