



DESCRIPTION:

Easy Entry Pre-Insulated Crimp Terminals are made from oxygen-free high conductivity copper. They are electro-tin plated for excellent conductivity and resistance to corrosion. Push-On terminals are made from brass, while the insulated types benefit from an additional internal copper sleeve, ensuring insulation support and a good crimp joint.

SPECIFICATION:

PVC:

MATERIAL: Electro-tin plated copper
INSULATION: Polyvinyl Chloride
APPROVALS: UL, E211389, RoHS compliant
MAX TEMPERATURE: 75°C
MAX VOLTAGE: 600V



NYLON:

MATERIAL: Electro-tin plated copper
INSULATION: Nylon
APPROVALS: UL, E211389, RoHS compliant
MAX TEMPERATURE: 105°C
MAX VOLTAGE: 600V



PART NUMBERS:

COLOUR/WIRE Ø mm ²	PART NO.		Max. elect. rating (A)	DIMENSIONS (mm)				PACK QTY
	PVC	NYLON		D	A	B	C	
0.5-1.5 RED	CIHBL1-3.2	CNIHBL1-3.2	19	4.10	28.0	3.0	18.0	100
	CIHBL1-4.6	CNIHBL1-4.6	19	4.10	28.0	4.6	18.0	100
1.5-2.5 BLUE	CIHBL2-3.2	CNIHBL2-3.2	27	4.50	28.0	3.0	18.0	100
	CIHBL2-4.6	CNIHBL2-4.6	27	4.50	28.0	4.6	18.0	100
4-6 YELLOW	CIHBL3-3.2	CNIHBL3-3.2	48	6.50	30.0	3.0	17.5	50
	CIHBL3-4.6	CNIHBL3-4.6	48	6.50	30.0	4.6	17.5	50



Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.
Phone: 01582 606033 • **Fax:** 01582 606063 • **Email:** sales@cablecraft.co.uk • **Web:** www.cablecraft.co.uk

VAT NO. GB 639 920 900 • CO. REG. NO. 2478297