

Our high quality self-extinguishing cable ties, are made from Nylon 6.6 and are available in either black or natural. They can be quickly and easily installed either by hand or with one of our tensioning tools. Ideal for securing cables, pipes and hoses. Used successfully in the most demanding industrial applications.

SPECIFICATION:

COLOUR OPTIONS: Natural or Black
MATERIAL: Nylon 6.6
SERVICE TEMPERATURE RANGE: -25°C to +85°C
HUMIDITY ABSORPTION: 2.5% (50% Relative Humidity)
TIGHTENING TEMPERATURE: -10°C to +60°C
MAX. ADMISSIBLE POINT: +110°C (For Short Time)
FUSION TEMPERATURE: +256°C
LIMIT OXYGEN INDEX (LOI): 27%
FLAMMABILITY RATING: UL 94 CLASS V2
DIELECTRIC STRENGTH: 50,000 Volts/mm
WEATHER RESISTANCE: High resistance to bases, oils, greases, oil derivatives, chloride solvents; limited resistance to acids; not resistant to phenols; halogen-free resins.
STANDARDS: UL: E1 60935. Lloyds R: 00/00017.



PART NUMBERS:

PART NO. NATURAL	PART NO. BLACK	WIDTH (mm)	LENGTH (mm)	MAX. BUNDLE DIA. (mm)	MIN. TENSILE STRENGTH Kg	PACK QTY
CTR 100-2.5N	CTR 100-2.5B	2.5	98	24	11	1000
CTR 160-2.5N	CTR 160-2.5B		160	40	11	1000
CTR 200-2.5N	CTR 200-2.5B		200	55	11	1000
CTR 140-3.6N	CTR 140-3.6B	3.5	140	36	20	1000
CTR 200-3.6N	CTR 200-3.6B		200	55	20	100
CTR 300-3.6N	CTR 300-3.6B		280	80	20	100
CTR 160-4.8N	CTR 160-4.8B	4.5	160	38	28	100
CTR 200-4.8N	CTR 200-4.8B		200	51	28	100
CTR 300-4.8N	CTR 300-4.8B		300	82	28	100
CTR 370-4.8N	CTR 370-4.8B		360	101	28	100
CTR 200-7.6N	CTR 200-7.6B	7.5	240	48	65	100
CTR 300-7.6N	CTR 300-7.6B		300	76	65	100
CTR 370-7.6N	CTR 370-7.6B		365	101	65	100
CTR 450-7.6N	CTR 450-7.6B		450	130	65	100
CTR 540-7.6N	CTR 540-7.6B		540	160	65	100
CTR 750-7.6N	CTR 750-7.6B		750	220	65	100
CTR 780-9.0N	CTR 780-9.0B	9.0	780	235	80	100
HEAVY DUTY ONLY AVAILABLE IN BLACK	CTR 500HDB	12.5	500	140	120	50
	CTR 720HDB		750	222	120	50
	CTR 1000HDB		1000	300	120	50



CABLECRAFT
creative wiring solutions



INVESTORS
IN PEOPLE



Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.
Phone: 01582 606033 • Fax: 01582 606063 • Email: sales@cablecraft.co.uk • Web: www.cablecraft.co.uk

VAT NO. GB 639 920 900 • CO. REG. NO. 2478297

UPDATED 20-06-17