



## DESCRIPTION:

This flexible, galvanised steel conduit with PVC cover has good mechanical stability and flexibility. Ideal for applications in machine tooling and connections for general factory wiring where light mechanical stress may occur.

## SPECIFICATION:

**MATERIAL:** Galvanised Steel & PVC Coating

**SERVICE TEMPERATURE RANGE:** -20°C to +80°C

**IP RATING:** IP 67

**CRUSH RESISTANCE:** To 1500N

**STANDARDS:** EN 500086 - DIN 53210

## PART NUMBERS:

PART NO.	CONDUIT SIZE (mm)	OUTSIDE DIA. (mm)	INSIDE DIA. (mm)	REEL QTY (m)	REEL QTY (m)
GSP20 (LENGTH)	20	21	17	10	30
GSP25 (LENGTH)	25	27	22	10	30
GSP32 (LENGTH)	32	34	28.1	10	30
GSP50 (LENGTH)	50	55	48	10	30
GSP63 (LENGTH)	63	65	57	10	30
GSP75 (LENGTH)	75	77	70	10	30
GSP100 (LENGTH)	100	102	93	10	30



**CABLECRAFT**  
creative wiring solutions



Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.  
**Phone:** 01582 606033 • **Fax:** 01582 606063 • **Email:** sales@cablecraft.co.uk • **Web:** www.cablecraft.co.uk

VAT NO. GB 639 920 900 • CO. REG. NO. 2478297