



Braided sleeving is lightweight, self-fitting and flexible. It is available in convenient mini packs, suitable for use with cables up to a maximum diameter of 55mm. It provides tough protection for bundles, wires, cables and flexible pipe systems. Ideal for use in automotive, rail traction and rolling stock, aerospace, military vehicles, submarines, ships and data telecommunications.

SPECIFICATION:

COLOUR OPTIONS: Black or Grey.
MATERIAL: Heat Stabilised Polyester
MONOFILAMENT: Polyester Size 0.22mm.
MELTING POINT: +250°C
LIMITING OXYGEN INDEX: 34%
CONTINUOUS TEMPERATURE: -50°C to +150°C
MAXIMUM WORKING TEMPERATURE: +250°C
FLAME RESISTANCE: Passes Flame Requirement of CEI 332-1, FMVSS 302(Type A) 12 According to NF F 16-101
FUMES TOXICITY/OPACITY: Passes CEI 754-1, CE 754/2, Low Smoke, NFC20452 (Polymer)
CHEMICAL RESISTANCE: Unaffected by most chemicals.



PART NUMBERS:

PART NO. BLACK	PART NO. GREY	MINIMUM DIA. (mm)	MAXIMUM DIA. (mm)	BOX QTY (m)
MBB-10-BLK	MBB-10-GRY	8	14	10
MBB-15-BLK	MBB-15-GRY	12	20	10
MBB-20-BLK	MBB-20-GRY	18	25	10
MBB-30-BLK	MBB-30-GRY	26	35	10
MBB-40-BLK	MBB-40-GRY	35	45	10
MBB-50-BLK	MBB-50-GRY	45	55	10



CABLECRAFT
creative wiring solutions



Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.
Phone: 01582 606033 • **Fax:** 01582 606063 • **Email:** sales@cablecraft.co.uk • **Web:** www.cablecraft.co.uk

VAT NO. GB 639 920 900 • CO. REG. NO. 2478297