



DESCRIPTION:

Our high quality Nylon cable ties are made from Nylon 6.6 and are available in various colours, particularly useful for identification purposes.

They can be quickly and easily installed either by hand or with one of our tensioning tools. Ideal for securing cables, pipes and hoses.

SPECIFICATION:

- COLOUR OPTIONS:** Red, Yellow, Green or Blue.
- MATERIAL:** Nylon 6.6
- SERVICE TEMPERATURE RANGE:** -25°C to +85°C
- HUMIDITY ABSORPTION:** 2.5% (50% Relative Humidity)
- TIGHTENING TEMPERATURE:** -10°C to +60°C
- MAX. ADMISSIBLE POINT:** +110°C (For Short Time)
- FUSION TEMPERATURE:** +256°C
- LIMIT OXYGEN INDEX (LOI):** 27%
- FLAMMABILITY RATING:** UL 94 CLASS V2
- DIELECTRIC STRENGTH:** 50,000 Volts/mm
- WEATHER RESISTANCE:** High resistance to bases, oils, greases, oil derivatives, chloride solvents; limited resistance to acids; not resistant to phenols; halogen-free resins.
- STANDARDS:** UL: E160935. Lloyds R: 00/00017.



HOW TO ORDER:
Add the required colour to the end of the part number.

PART NUMBERS:

PART NUMBER	WIDTH (mm)	LENGTH (mm)	MAX. BUNDLE DIA. (mm)	MIN. TENSILE STRENGTH	PACK QTY.
CTR100-2.5 (COLOUR)	2.5	100	48	9	100
CTR140-3.5 (COLOUR)	3.5	140	36	20	100
CTR200-4.8 (COLOUR)	4.5	200	51	28	100
CTR300-4.8 (COLOUR)		280	76	28	100



Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.
Phone: 01582 606033 • **Fax:** 01582 606063 • **Email:** sales@cablecraft.co.uk • **Web:** www.cablecraft.co.uk

VAT NO. GB 639 920 900 • CO. REG. NO. 2478297