



Our brass dome top glands offer high quality and total reliability. Suitable for use in plant and automation technologies where exceptional and safe functioning are required. Suitable for high demands, offering excellent strain relief.

SPECIFICATION:

MATERIAL: Brass Nickel Plated

PROTECTION CLASS: IP68

TEMPERATURE RANGE: -40°C to +100°C

CLAMPING INSERT: Polyamide 6

SEALING RING: Neoprene



METRIC GLANDS

PART NO.	THREAD SIZE	TD (HOLE SIZE mm)	TL (LENGTH OF THREAD mm)	FOR CABLE RANGE MIN-MAX Ø (mm)	PACK QTY
EPN 700/M12	M 12 x 1.5	12.0	6.0	3.0 - 6.5	1
EPN 700/M16	M 16 x 1.5	16.0	7.0	4.0 - 8.0	1
EPN 700/M20	M 20 x 1.5	20.0	8.0	6.0 - 12.0	1
EPN 700/M25	M 25 x 1.5	25.0	8.0	10.0 - 14.0	1
EPN 700/M32	M 32 x 1.5	32.0	9.0	13.0 - 18.0	1
EPN 700/M40	M 40 x 1.5	40.0	9.0	18.0 - 25.0	1
EPN 700/M50	M 50 x 1.5	50.0	9.0	22.0 - 32.0	1
EPN 700/M63	M 63 x 1.5	63.0	14.0	34.0 - 44.0	1

METRIC LOCKNUTS

PART NO.	THREAD SIZE	DEPTH (mm)	PACK QTY
EPN 710/M12	M 12 x 1.5	2.8	1
EPN 710/M16	M 16 x 1.5	3.0	1
EPN 710/M20	M 20 x 1.5	3.5	1
EPN 710/M25	M 25 x 1.5	4.0	1
EPN 710/M32	M 32 x 1.5	5.0	1
EPN 710/M40	M 40 x 1.5	5.0	1
EPN 710/M50	M 50 x 1.5	5.0	1
EPN 710/M63	M 63 x 1.5	5.0	1



CABLECRAFT
creative wiring solutions



Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.
Phone: 01582 606033 • **Fax:** 01582 606063 • **Email:** sales@cablecraft.co.uk • **Web:** www.cablecraft.co.uk

VAT NO. GB 639 920 900 • CO. REG. NO. 2478297