


**DESCRIPTION:**

A flexible grommet strip in natural LDPE, this is supplied in poly bags and can be easily cut. Suitable for a range of panel thicknesses from 0.8mm to 4.0mm.



**SPECIFICATION:**

<b>MATERIAL:</b> Non-flame retardant halogen free LDPE
<b>COLOUR:</b> Natural
<b>OPERATING TEMPERATURE:</b> -50°C to +50°C
<b>DIMENSIONS (NOM. DIA):</b> 4.0 - 20mm.
<b>DIELECTRIC STRENGTH:</b> 60kV/mm
<b>TENSILE STRENGTH AT BREAK:</b> 12 MPa



**PART NUMBERS:**

PART NUMBER	PANEL THICKNESS (mm)	A (mm)	B (mm)	C (mm)	D (mm)	PACK QUANTITY
CGSS 1	0.8-1.0	1.0	2.0	3.0	3.2	35
CGSS 2	1.1-1.5	1.5	2.0	3.5	3.2	30
CGSS 3	1.6-2.0	2.0	3.0	4.3	4.3	25
CGSS 4	2.1-3.0	3.0	3.0	5.3	4.3	20
CGSS 5	3.1-4.0	4.0	3.5	6.9	5.3	15



Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.  
**Phone:** 01582 606033 • **Fax:** 01582 606063 • **Email:** sales@cablecraft.co.uk • **Web:** www.cablecraft.co.uk

VAT NO. GB 639 920 900 • CO. REG. NO. 2478297