

Neoprene sleeves are made from highly elastic extruded Polychloroprene rubber, pre-lubricated as standard (CH12-CH25). They are particularly useful for binding the ends of braided mains leads into plugs and portable equipment. The sleeves can be stretched 5 times in fitting and 2 times in use. Neoprene sleeves are best applied using the expanding tools. Available in 12 colours for easy identification, diameters range from 1.2mm to 20mm. Custom lengths are available to order.

SPECIFICATION:

COLOUR OPTIONS: Black, Blue, Brown, Green, Grey, Orange, Pink, Red, Violet, White, Yellow, Green/Yellow.

MATERIAL: Polychloroprene Rubber Quality 3490

SERVICE TEMPERATURE RANGE: -30°C to +90°C

SHORT TIME TEMPERATURE: 110°C

Shore hardness a: 40 ± 5

TENSILE STRENGTH AT BREAK: >6.5 MPa

ULTIMATE ELONGATION: >500%

TEAR STRENGTH: 10kN/m

DIELECTRIC STRENGTH: 13 kv/mm

VOLUME RESISTIVITY: 4 x 109 cm

FLAME RESISTANCE: VO UL94

CHEMICAL RESISTANCE: Resistance to mineral and vegetable oils, aromatic fuels, acids and alkalis.

MATERIAL SPECIFICATION: BS3858 Type 1.

PART NUMBERS:

PRE-CUT LENGTHS				
PART NO.	LENGTH (mm)	INTERNAL DIA. (mm)	MAX. OD OF CABLE (mm)	PACK QTY
CH12x20 (COLOUR)	20	1.2	2.4	1000
CH15x20 (COLOUR)	20	1.5	3.0	1000
CH20x20 (COLOUR)	20	2.5	4.0	1000
CH30x25 (COLOUR)	25	3.0	6.0	1000
CH50x25 (COLOUR)	25	5.0	10.0	100
CH75x25 (COLOUR)	25	7.5	15.0	100
CH100x25 (COLOUR)	25	10.0	19.8	100
CH150x25 (COLOUR)	25	15.0	30.0	100
CH200x25 (COLOUR)	25	20.0	40.0	100



G CABLECRAFT COMPANY



CERTIFICATE NO. 9277



I.D. 22645





Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD. Phone: 01582 606033 • Fax: 01582 606063 • Email: sales@cablecraft.co.uk • Web: www.cablecraft.co.uk VAT NO. GB 639 920 900 • CO. REG. NO. 2478297

CABLECRAFT

creative wiring solutions



