



DESCRIPTION:

Cablecraft SRK 4/2A features two channel pluggable cross-connectors and a more rigid construction on the rail. The operating temperature is -40°C to +120°.

SPECIFICATION:

MATERIAL: Polyamide 6.6 UL 94 - V0

DIN RAIL TYPE: Foot can be snapped on to TS 35 DIN rail

STANDARDS: IEC, UL and CSA approved



OTHER COLOURS AVAILABLE



HOW TO ORDER:
Add the required colour to the end of the part number.

PART NUMBERS:



RATED VOLTAGE/MAX CURRENT

PART NUMBER	IEC	CONDUCTOR mm ² /AWG	PACK QUANTITY
TERMINAL BLOCK			
SRK4/2A - (COLOUR)	1000/41	4.0/26-10	1

ACCESSORY TYPE	PART NUMBER	PACK QUANTITY
SRK 4/2A ACCESSORIES		
End Plate	AP2.5-10	1
Partition Plate	TW4-10	1
Two Pole Insulated Cross Connector	SQI4/2	1
Three Pole Insulated Cross Connector	SQI4/3	1
Four Pole Insulated Cross Connector	SQI4/4	1
Ten Pole Insulated Cross Connector	SQI4/10	1
Thirty Pole Insulated Cross Connector	SQI4/30	1
End Stop - Snap On	SES35	1
End Stop - Snap On	ES35	1



Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.
Phone: 01582 606033 • **Fax:** 01582 606063 • **Email:** sales@cablecraft.co.uk • **Web:** www.cablecraft.co.uk

VAT NO. GB 639 920 900 • CO. REG. NO. 2478297