



DESCRIPTION:

Our spiral binding provides a fast, flexible, simple method of binding and protecting cable looms both before and after installation. It enables cable to be led out at any point.

APPLICATIONS:

For protecting cable looms before and after installation.

SPECIFICATION:

COLOUR OPTIONS: Black or Natural

MATERIAL: Low Density Polyethylene (LDPE)

SERVICE TEMPERATURE RANGE: -50°C to +50°C



PART NUMBERS:

PART NO.	COLOUR	INSIDE DIA. (mm)	WALL THICKNESS (mm)	PITCH BETWEEN LEAD OUT POINTS (mm)	RANGE OF LOOM DIA. (mm)	LENGTH PER COIL (m)
CSB 1N	Natural	6.5	0.75	10.0	7.0 - 40.0	25
CSB 1B	Black	6.5	0.75	10.0	7.0 - 40.0	25
CSB 2N	Natural	8.2	0.90	12.0	12.0 - 50.0	25
CSB 2B	Black	8.2	0.90	12.0	12.0 - 50.0	25
CSB 3N	Natural	12.0	1.00	16.0	15.0 - 80.0	20
CSB 3B	Black	12.0	1.00	16.0	15.0 - 80.0	20
CSB 4N	Natural	20.0	1.5	18.0	25.0 - 100.0	25
CSB 4B	Black	20.0	1.5	18.0	25.0 - 100.0	25



CABLECRAFT
creative wiring solutions



Cablecraft House, Circle Business Centre, Blackburn Road, Houghton-Regis, Bedfordshire, LU5 5DD.
Phone: 01582 606033 • **Fax:** 01582 606063 • **Email:** sales@cablecraft.co.uk • **Web:** www.cablecraft.co.uk

VAT NO. GB 639 920 900 • CO. REG. NO. 2478297