



Heavy duty copper tube angled palm terminals.

Key features.

- Manufactured from seamless copper tube to BS EN 12449: 1999
- Heat resistant up to 240 °C

Specification.

Material:
Seamless copper tube to BS EN 12449: 1999

Service temperature:
Heat resistant up to 240 °C

Approvals:
BS EN 61238-1-2003 and BS 4579



Cable size mm ²	Part no.	Stud size (mm)	Dimensions (mm)							Pack quantity
			A	B	W	E	F	D	T	
10	CCT10-5RA	5	6.9	4.4	11	9.0	9.0	9	2.0	1
	CCT10-6RA	6	6.9	4.4	11	9.0	9.0	9	2.0	1
	CCT10-8RA	8	6.9	4.4	11	9.0	9.0	11	1.6	1
	CCT10-10RA	10	6.9	4.4	16	10.5	10.5	10	1.5	1
16	CCT16-5RA	5	8.0	5.6	11	8.5	8.5	11	2.2	1
	CCT16-6RA	6	8.0	5.6	11	8.5	8.5	11	2.2	1
	CCT16-8RA	8	8.0	5.6	11	8.5	8.5	11	1.7	1
	CCT16-10RA	10	8.0	5.6	15	11	11	11	1.5	1
25	CCT25-5RA	5	9.5	7	13.5	9.75	8.25	13	2.4	1
	CCT25-6RA	6	9.5	7	13.5	9.75	8.25	13	2.4	1
	CCT25-8RA	8	9.5	7	13.5	9.75	8.25	13	2.4	1
	CCT25-10RA	10	9.5	7	16	12	10	13	2.0	1
35	CCT35-5RA	5	11.0	8.2	15.5	9.75	8.25	14	2.8	1
	CCT35-6RA	6	11.0	8.2	15.5	9.75	8.25	14	2.8	1
	CCT35-8RA	8	11.0	8.2	15.5	9.75	8.25	14	2.8	1
	CCT35-10RA	10	11.0	8.2	15.5	12	10	14	2.8	1

Cable size mm ²	Part no.	Stud size (mm)	Dimensions (mm)							Pack quantity
			A	B	W	E	F	D	T	
50	CCT50-5RA	5	12.1	9.5	17.5	9.0	9.0	18	2.4	1
	CCT50-6RA	6	12.1	9.5	17.5	9.0	9.0	18	2.4	1
	CCT50-8RA	8	12.1	9.5	17.5	9.0	9.0	18	2.4	1
	CCT50-10RA	10	12.1	9.5	17.5	9.0	9.0	18	2.4	1
	CCT50-12RA	12	12.1	9.5	17.5	11	11	18	2.4	1
70	CCT70-5RA	5	15.0	11.5	21.5	8.5	8.5	18	3.5	1
	CCT70-6RA	6	15.0	11.5	21.5	8.5	8.5	18	3.5	1
	CCT70-8RA	8	15.0	11.5	21.5	8.5	8.5	18	3.5	1
	CCT70-10RA	10	15.0	11.5	21.5	10.5	10.5	18	3.5	1
	CCT70-12RA	12	15.0	11.5	21.5	10.5	10.5	18	3.5	1
95	CCT95-8RA	8	17.0	13.5	24.3	13	10	24	3.5	1
	CCT95-10RA	10	17.0	13.5	24.3	13	10	24	3.5	1
	CCT95-12RA	12	17.0	13.5	24.3	13	10	24	3.5	1
	CCT95-14RA	14	17.0	13.5	21.2	13	10	24	3.5	1
120	CCT120-10RA	10	19.0	15.0	27.2	16.5	16.5	27	4	1
	CCT120-12RA	12	19.0	15.0	27.2	16.5	16.5	27	4	1
	CCT120-14RA	14	19.0	15.0	27.2	16.5	16.5	27	4	1
150	CCT150-10RA	10	21.0	16.5	30	16.5	16.5	27	4.5	1
	CCT150-12RA	12	21.0	16.5	30	16.5	16.5	27	4.5	1
	CCT150-14RA	14	21.0	16.5	30	16.5	16.5	27	4.5	1
185	CCT185-12RA	12	23	18.5	33.5	16.5	16.5	30	4.5	1
	CCT185-14RA	14	23	18.5	33.5	16.5	16.5	30	4.5	1
	CCT185-16RA	16	23	18.5	33.5	16.5	16.5	30	4.5	1
240	CCT240-10RA	10	26.0	21.0	37.7	18	17	32	5	1
	CCT240-12RA	12	26.0	21.0	37.7	18	17	32	5	1
	CCT240-14RA	14	26.0	21.0	37.7	18	17	32	5	1
	CCT240-16RA	16	26.0	21.0	37.7	18	17	32	5	1
300	CCT300-12RA	12	28.0	23.0	41	18	17	37	5	1
	CCT300-14RA	14	28.0	23.0	41	18	17	37	5	1
	CCT300-16RA	16	28.0	23.0	41	18	17	37	5	1
400	CCT400-12RA	12	32.0	27.0	47.3	25	25	38	5	1
	CCT400-14RA	14	32.0	27.0	47.3	25	25	38	5	1
	CCT400-16RA	16	32.0	27.0	47.3	25	25	38	5	1
500	CCT500 RA	ANY	38.1	30	55	29	25	44	8.2	1
630	CCT630 RA	ANY	44	33.8	63	25	23	46	10.2	1
800	CCT800 RA	ANY	49	38	70	34	34	56	11	1
1000	CCT1000 RA	ANY	53	42.5	77	34	34	56	10.5	1