

**ELAND**<sup>®</sup>  
CABLES

# Veriflex<sup>®</sup> CY PVC (YSLCY) Control Cable



Eland Product Group: V03

## APPLICATION

Veriflex<sup>®</sup> screened flexible connecting cables for instrumentation and control equipment, for tooling machinery production lines and, in flexible applications for free movement without tensile load. Suitable for use in dry, moist and wet rooms. These cables are not used for outdoor or underground installation.

CY control cables are not suitable for fixed wiring applications requiring compliance with the regulations set out in BS7671.

## CHARACTERISTICS

### Voltage Rating

300/500V

### Test Voltage

4kV

### Temperature Rating

Fixed: -40°C to +80°C

Flexed: -5°C to +70°C

### Minimum Bending Radius

Fixed: 4 x overall diameter

Flexed: 12.5 x overall diameter

## CONSTRUCTION

### Conductor

Class 5 flexible plain copper wires

### Insulation

PVC (Polyvinyl Chloride)

### Separator

PET (Polyester Tape)

### Screen

TCWB (Tinned Copper Wire Braid)

### Sheath

PVC (Polyvinyl Chloride)

### Core Identification

● Black with white number

From 3 cores: ● Black with white number + ● Green/Yellow

Colour-coded cores available upon request

### Sheath Colour

● Grey

## BSI KITEMARK™ TESTED



Cables are tested and verified by The Cable Lab<sup>®</sup> to confirm they meet the quality standards required of the BSI Cable Batch Verification Kitemark™

## STANDARDS


VDE 0207-363-3, VDE 0285-525-2-51, VDE 0285-525-1, VDE 0285-525-2-11, VDE 0482-332-1-2, VDE 819-102 (TM54)

Flame Retardant according to IEC 60332-1-2



## UK LABORATORY TESTED

This product is subject to the Quality Assurance protocols of The Cable Lab<sup>®</sup>, a UKAS accredited ISO 17025 cable testing laboratory. Testing includes vertical flame, conductor resistance, tensile & elongation, and dimensional consistency, verified to published standards and approved product drawings.



## REGULATORY COMPLIANCE

This cable meets the requirements of the Low Voltage Directive 2014/35/EU and the RoHS Directive 2011/65/EU. RoHS compliance has been tested and confirmed by The Cable Lab<sup>®</sup> as meeting the requirements of the BSI RoHS Trusted Kitemark™.



## DIMENSIONS

ELAND PART NO.	NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	NOMINAL THICKNESS OF INSULATION mm	NOMINAL OUTER SHEATH THICKNESS mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km	HUMMEL EMC EARTHING GLAND SIZE
V0302001GR000	2	0.5	0.40	0.6	5	35	16
V0302011GR000	2	0.75	0.40	0.6	5.5	45	16
V0302021GR000	2	1	0.40	0.7	6.1	56	16
V0302031GR000	2	1.5	0.40	0.7	6.7	69	16
V0303001GR000	3	0.5	0.40	0.6	5.4	48	16
V0303011GR000	3	0.75	0.40	0.7	6	61	16
V0303021GR000	3	1	0.40	0.7	6.4	71	16
V0303031GR000	3	1.5	0.40	0.7	7.1	90	16
V0303041GR000	3	2.5	0.50	0.8	8.6	136	20
V0304001GR000	4	0.5	0.40	0.7	6	61	16
V0304011GR000	4	0.75	0.40	0.7	6.5	75	16
V0304021GR000	4	1	0.40	0.7	7	89	16
V0304031GR000	4	1.5	0.40	0.7	7.7	114	16
V0304041GR000	4	2.5	0.50	0.8	9.4	173	20
V0304051GR000	4	4	0.60	1	11.5	260	25
V0304061GR000	4	6	0.65	1.1	13.1	358	32
V0304071GR000	4	10	0.75	1.3	16.7	593	32
V0304081GR000	4	16	0.75	1.5	19	852	40
V0304091GR000	4	25	0.90	1.6	23.5	1274	40
V0304101GR000	4	35	0.95	1.7	26.9	1686	50
V0305001GR000	5	0.5	0.40	0.7	6.5	73	16
V0305011GR000	5	0.75	0.40	0.7	7	89	16
V0305021GR000	5	1	0.40	0.7	7.6	107	16
V0305031GR000	5	1.5	0.40	0.8	8.6	142	20
V0305041GR000	5	2.5	0.50	0.9	10.4	216	25
V0305071GR000	5	10	0.75	1.4	18.5	738	32
V0305081GR000	5	16	0.75	1.5	20.9	1050	40
V0305091GR000	5	25	0.90	1.7	26.1	1588	50
V0307001GR000	7	0.5	0.40	0.7	7	89	16
V0307011GR000	7	0.75	0.40	0.7	7.6	112	16
V0307021GR000	7	1	0.40	0.8	8.4	139	20
V0307031GR000	7	1.5	0.40	0.8	9.3	180	20
V0307041GR000	7	2.5	0.50	1	11.5	283	25
V0312001GR00000	12	0.5	0.40	0.8	9.2	143	20
V0312011GR00000	12	0.75	0.40	0.8	10	181	20
V0312021GR00000	12	1	0.40	1	11.2	230	25
V0312031GR00000	12	1.5	0.40	1.1	12.7	307	32
V0318011GR000	18	0.75	0.40	1.1	12.2	274	25
V0318021GR000	18	1	0.40	1.1	13.2	331	32
V0318031GR000	18	1.5	0.40	1.2	14.9	443	32
V0325011GR000	25	0.75	0.40	1.1	13.2	282	32
V0325021GR000	25	1	0.40	1.2	15.8	444	32
V0325031GR000	25	1.5	0.40	1.3	17.9	596	32

## ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA mm <sup>2</sup>	CURRENT CARRYING CAPACITIES 30°C CONTINUOUS LOADING A	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km
0.5	9	39
0.75	12	26
1	15	19.5
1.5	18	13.3
2.5	26	7.98
4	34	4.95
6	44	3.3
10	61	1.91
16	82	1.21
25	108	0.780
35	135	0.554

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.