

Wireless Bolt™

Anybus Wireless Bolt enables you to connect industrial machinery to a wireless network. It is attached onto a cabinet or a machine to enable wireless access.

Wireless transmission is made via Bluetooth or Wireless LAN technology. The wired connection is made using Ethernet.



EXAMPLE USE CASE



The Wireless Bolt is typically used for configuration purposes. For example, you can bring your own device (BYOD) such as a tablet to a machine and use it as an HMI. Another typical use case is connecting a machine to a cloud service.

Availability

Anybus Wireless Bolt Ethernet.
Bluetooth access point or client.
WLAN 2.4 GHz/5 GHz access point or client.

AWB2000

18-pole push spring connector

AWB2000-B-RJ45PACK

18-pole push spring connector with RJ45 adapter pre-assembled

AWB2030

RJ45 connector and PoE (Power over Ethernet)

Accessories

024703

Bolt cable kit. Bolt connector with Ethernet cable (RJ45 male) and power supply (World) with cable. Both cables are 150cm. (for AWB2000 only)

024704

Bolt RJ45 Adapter. Bolt connector with Ethernet cable (RJ45 female). Total length 20 cm. (for AWB2000 only)

AWB4005

PoE Injector, 100-240VAC

AWB4006

PoE Injector, 12-57VDC



HMS provides a full 3 year product guarantee

Use your laptop, phone or tablet instead of an HMI

Connect a Wireless Bolt to your machine and access the internal web pages via a laptop, tablet or smartphone. BYOD (Bring Your Own Device) means that you no longer need an expensive HMI.

Multipoint or point-to-point

Anybus Wireless Bolt is often used as an access point for several WLAN/Bluetooth nodes, but it can also be used as an Ethernet cable replacement (point-to-point communication).

Features and benefits

- Range up to 100 meters.
- Rugged design with IP67-classed housing.
- Easy configuration via built-in web configuration pages.
- Mounted by making an M50 hole (50.5 mm) in the host cabinet/machine. The bottom part of the Bolt goes inside the cabinet and the top part is located on the outside.
- All-in-one package: Connector, communication hardware and integrated antenna in the same unit.
- Connects to your machine via Ethernet.
- Simultaneous operation of Bluetooth and WLAN allowing for bridging between the two.
- PoE (Power over Ethernet) for RJ45-version.

Which wireless standard?

Use WLAN (aka WiFi) if:

- Interaction with other devices is needed, e.g. Bolt/AWB II to tablet/PC/phone or WLAN infrastructure.
- WLAN channel frequency planning is possible.
- Higher data throughput speed is necessary.
- Larger file transfers are expected.

Use Bluetooth if:

- The wireless link has Anybus products in both ends, e.g. Bolt to Bolt, AWB II to AWB II or Bolt to AWB II.
- A robust and reliable link without interruptions is important e.g. in an industrial environment with lots of disturbances, and maybe has been proven not to work well using WLAN.
- A Profinet or Ethernet/IP I/O cycle time of 64ms or higher is acceptable.
- The data throughput speed need is on the lower side.

TECHNICAL SPECIFICATIONS



AWB2000

AWB2030



Type of wired interface	Ethernet	
Order code	AWB2000	AWB2030
Connector	Included plug connector (2x9p; 3.5mm, Phoenix DFMC 1.5/9-ST-3.5, push-in spring connection).	RJ45 Ethernet/PoE, 3 Pole screw connector for power
Range	100 meters	
Antenna	Built-in	
Operating temperature	-40 to +65 °C (Storage temperature: -40 to +85 °C)	
Weight	81 g	84 g
Housing material	Top: Valox 357X(f1) PBT/PC. Suitable for outdoor use with respect to exposure to ultraviolet light, water exposure and immersion in accordance with UL 476C. Bottom: Celanex: XFR 6840 GF15. PBT glass reinforced plastic.	
IP protection class	IP67 and UL NEMA 4X for top (outside the host), IP21 for bottom (inside the host).	
Dimensions	Diameter: 68 mm. Height: 75 mm (95 mm including connector). Outside height: 41 mm.	Diameter: 68 mm. Height: 75 mm without PS-connector, 84 mm incl. PS-connector. Outside height: 41 mm.
Mounting	M50 screw and nut (50.5 mm hole needed).	
Power	9-30 VDC (-5% +20%), Cranking 12V (ISO 7637-2:2011 pulse 4). Reverse polarity protection. (Consumption: 0.7W idle, 1.7W max.)	19-36 VDC, PoE (Power over Ethernet) DTE Type1 according to IEEE 802.3af.
Configuration	Three different methods: • Accessing the built-in web pages in the product • Sending AT-commands via Telnet/Raw TCP • Using Easy Config modes	
Vibration compatibility:	Sinusoidal vibration test according to IEC 60068-2-6:2007 and with extra severities; Number of axes: 3 mutually perpendicular (X:Y:Z), Duration: 10 sweep cycles in each axes, Velocity: 1 oct/min, Mode: in operation, Frequency: 5-500 Hz, Displacement ±3.5 mm, Acceleration: 2g. Shock test according to IEC 60068-2-27:2008 and with extra severities; Wave shape: half sine, Number of shocks: ±3 in each axes, Mode: In operation, Axes ± X,Y,Z, Acceleration: 30 m/s ² , Duration: 11 ms.	
Humidity compatibility:	EN 60068-2-78: Damp heat, +40°C, 93% humidity for 4 days.	

COMMUNICATION WITH HOST DEVICE

Digital input	Usage: To control roaming between access points. (max 3 m signal cable).	None
Ethernet	10/100BASE-T with automatic MDI/MDIX auto cross-over detection. Supported Ethernet protocols: IP, TCP, UDP, HTTP, LLDP, ARP, DHCP Client/Server, DNS support. PROFINET IO, EtherNet/IP, Modbus-TCP. (SNMP user management and access control in pending release.)	

WIRELESS STANDARDS

WLAN	Wireless standards: WLAN 802.11 a, b, g, n. (n in pending release) Operation modes: Access point or Client WiFi channels: 2.4 GHz, channel 1-11. 5 GHz Access Point: 36-48 (U-NII-1), 5 GHz Client: 36-140 (U-NII-1, U-NII-2A, U-NII-2C). RF output power: 16 dBm WLAN conducted sensitivity: 2.4 GHz: -95 dBm. 5 GHz: -90 dBm. Max number of slaves for access point: 7 Power consumption: 54mA@24VDC Net data throughput: 20 Mbps. Link speed: 54 Mbps (802.11 g) Security: WEP 64/128, WPA, WPA-PSK and WPA2, LEAP, PEAP (MS-CHAP pending).	
Bluetooth	Wireless standards (profiles): PANU & NAP Operation modes: Access point or Client RF output power: 10 dBm Bluetooth conducted sensitivity: -90 dBm Max number of slaves for access point: 7 Power consumption: 36 mA@24VDC Net data throughput: ~1 Mbps Bluetooth version support: v4.0 Security: Authentication & Authorization, Encryption & Data Protection, Privacy & Confidentiality, NIST Compliant, FIPS Approved	
Bluetooth Low Energy (Pending release)	Wireless standards (profiles): GATT Operation modes: Central or Peripheral RF output power: 7 dBm Max number of slaves for Central: 10 Power consumption: 36 mA@24VDC Net data throughput: ~200 kbps Bluetooth version support: v4.0 Security: AES-CCM cryptography	


CERTIFICATIONS

Europe	ATEX Category 3, zone 2 according to EN60079-15, product marking: EX II 3 G nA IIC T4 Gc. CE, 2014/53/EU Radio Equipment Directive (RED)	ATEX Category 3, zone 2 according to EN60079-15, product marking: EX II 3 G nA IIC T4 Gc (pending). CE, 2014/53/EU Radio Equipment Directive (RED)
U.S.	FCC 47 CFR part 15, subpart B. UL: Ind. Cont. Eq. also Listed Ind. Cont. Eq. for Haz. Loc. CL1, DIV 2, GP A,B,C,D. UL file: E203225	FCC 47 CFR part 15, subpart B. UL: Ind. Cont. Eq. also Listed Ind. Cont. Eq. for Haz. Loc. CL1, DIV 2, GP A,B,C,D. UL file: E203225 (pending)
Canada	ICES-003	ICES-003
Japan	MIC	MIC
Other countries	Australia, Colombia, Turkey, Malaysia Pending: Brazil, Argentina, India	-



Mounting

The Anybus Wireless Bolt is mounted into a 50.5 mm (M50) hole in the host device. The top ("helmet") goes on the outside and provides an IP67 exterior. The bottom is located inside the machine or cabinet (IP21).



Configuration

You can configure the Anybus Wireless Bolt by accessing the built-in web pages in the product. You can also send AT commands or use Easy Config modes.



Bolt Cable Kit

Bolt connector with Ethernet cable (RJ45 male) and power supply (World) with cable. Both cables are 150cm. Order code: 024703 (AWB2000 only)

Bolt RJ45 Adapter

Bolt connector with Ethernet cable (RJ45 female). Total length 20 cm. Order code: 024704 (AWB2000 only)



Order a Starter Kit!

Includes: Two Wireless Bolts, Power Supply (world), cabling, Quick Start Guide. Order code: AWB2300

Anybus® is a registered trademark of HMS Industrial Networks AB, Sweden, USA, Germany and other countries. Other marks and words belong to their respective companies.

All other product or service names mentioned in this document are trademarks of their respective companies.

Part No: MMA434 Version 16 05/2018 - © HMS Industrial Networks - All rights reserved - HMS reserves the right to make modifications without prior notice.