

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com







The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Туре	HDC 16A TSLU 1M25G
Order No.	<u>1788740000</u>
Version	HDC enclosures, Size: 5, Protection degree: IP65, Cable entry from side, Plug housing, End-locking clamp, lower side, Standard, Size of cable entries: M 25
GTIN (EAN)	4032248206285
Qty.	1 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Dimensions and weights

Width	32.5 mm	Width (inches)	1.28 inch
Height	58 mm	Height (inches)	2.283 inch
Depth	89 mm	Depth (inches)	3.504 inch
Net weight	125 g		

Temperatures

Limit temperature -40 °C ... 125 °C

Environmental Product Compliance

REACH SVHC Lead 7439-92-1, DIBP 84-69-5

Dimensions

Cable entry	w. threading	Height of housing B	58 mm	
Total length housing	79 mm	Width housing C	29.5 mm	

General data

EMC housings	No	Housing main material	diecast aluminium
Material of locking element	Stainless steel, rust-proof	Protection degree	IP65
Surface finish	Powder coating	Tightening torque	0.5 Nm

Version

Cable entry	w. threading	Clamp version	End-locking clamp
Design		Design of housing	Cable entry from side, Plug
	Standard		housing
Design of locking system	End-locking clamp, lower	Internal thread	
	side		M 25
Number of cable entry on top	0	Number of cable entry sideways	1
Sealing	NBR	Size	5
Size of cable entries	M 25	Suitable for ModuPlug [®]	No
Tightening torque	0.5 Nm	Top part/bottom part/lid	upper part
Туре	Plug		

Classifications

ETIM 6.0	EC000437	ETIM 7.0	EC000437
eClass 9.0	27-44-02-02	eClass 9.1	27-44-02-02
eClass 10.0	27-44-02-02	UNSPSC	30-21-18-01

Approvals

Approvals





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Downloads

Brochure/Catalogue	CAT 3 HDC 17/18 EN	
	FL FIELDWIRING EN	
Engineering Data	EPLAN, WSCAD	
Engineering Data	<u>STEP</u>	
Technical Documentation	1788740000_HDC_16A_TSLU_1M25G_STP_Blatt1.pdf	




Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Drawings





HDC enclosures

HDC 16A TSLU 1M25G

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Coupling housing



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Туре	HDC 16A KLU 1M25G	Version
Order No.	<u>1788800000</u>	HDC enclosures, Size: 5, Protection degree: IP65, Closed housing, End-
GTIN (EAN)	4032248206346	locking clamp, lower side, Standard, Size of cable entries: M 25
Qty.	1 pc(s).	
Туре	HDC 16A KLU 1PG16G	Version
Type Order No.	HDC 16A KLU 1PG16G 1665450000	Version HDC enclosures, Size: 5, Protection degree: IP65, Closed housing, End-
• •		



Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Cover



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Туре	HDC 16A DMDL 2BO	Version
Order No.	<u>1665910000</u>	HDC enclosures, Size: 5, Protection degree: IP65, Cover for upper part
GTIN (EAN)	4008190422943	of housing, End-locking clamp, lower side, Standard
Qty.	1 pc(s).	

Base housing



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Туре	HDC 16A SLU 2PG16G	Version
Order No.	<u>1665070000</u>	HDC enclosures, Size: 5, Protection degree: IP65, Closed base, End-
GTIN (EAN)	4008190421779	locking clamp, lower side, Standard, Size of cable entries: PG 16
Qty.	1 pc(s).	
Туре	HDC 16A SLU 2M20G	Version
Type Order No.	HDC 16A SLU 2M20G 1788770000	Version HDC enclosures, Size: 5, Protection degree: IP65, Closed base, End-
• •		

Creation date 10 December 2019 16:37:05 CET



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Type	HDC 16A SLU 2M25G	Version
Order No.	<u>1788760000</u>	HDC enclosures, Size: 5, Protection degree: IP65, Closed base, End-
GTIN (EAN)	4032248206308	locking clamp, lower side, Standard, Size of cable entries: M 25
Qty.	1 pc(s).	
Туре	HDC 16A SLU 1PG21G	Version
Type Order No.	HDC 16A SLU 1PG21G 1665090000	Version HDC enclosures, Size: 5, Protection degree: IP65, Closed base, End-

Bulkhead housing



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Туре	HDC 16A ALU	Version
Order No.	<u>1664920000</u>	HDC enclosures, Size: 5, Protection degree: IP65, Open base, End-
GTIN (EAN)	4008190421625	locking clamp, lower side, Standard
Qty.	1 pc(s).	