

**Crimping contact  
HDC-C-HE-SM1.5AG**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Crimps provide a electrical and mechanical connection between wire and contact that is both secure and reliable. The optimal crimp connection is gas-tight and corrosion-resistant.

**General ordering data**

|            |  |
|------------|--|
| Type       | HDC-C-HE-SM1.5AG   |
| Order No.  | <a href="#">1200700000</a>   |
| Version    | Heavy Duty Connectors, Crimp contact, HE, HEE, HQ, MixMate, Male, Conductor cross-section, max.: 1.5, turned, Copper alloy |
| GTIN (EAN) | 4008190074920  |
| Qty.       | 100 pc(s).   |

**Crimping contact  
HDC-C-HE-SM1.5AG**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data**

**Dimensions and weights**

|            |        |          |        |
|------------|--------|----------|--------|
| Net weight | 1.33 g | Diameter | 4.5 mm |
|------------|--------|----------|--------|

**Environmental Product Compliance**

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

**General data**

|                                    |                      |                                  |                     |
|------------------------------------|----------------------|----------------------------------|---------------------|
| Contact diameter, male Ø           | 2.5 mm               | Cross-section for connected wire | 1.5 mm <sup>2</sup> |
| Material                           | Copper alloy         | Plugging cycles                  | ≥ 500               |
| Production methods                 | turned               | Series                           | HE                  |
| Stripping length, rated connection | 7.5 mm               | Surface finish                   | silver              |
| Type                               | Male                 | Type of connection               | Crimp connection    |
| Version insert                     | HE, HEE, HQ, MixMate | Volume resistance                | ≤ 2mΩ               |

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000796    | ETIM 4.0   | EC000796    |
| ETIM 5.0   | EC000796    | ETIM 6.0   | EC000796    |
| UNSPSC     | 30-21-18-01 | eClass 5.1 | 27-14-34-19 |
| eClass 6.2 | 27-26-12-02 | eClass 7.1 | 27-44-02-04 |
| eClass 8.1 | 27-44-02-04 | eClass 9.0 | 27-44-02-04 |
| eClass 9.1 | 27-44-02-04 |            |             |

**Approvals**

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                    |   |
|--------------------|---|
| Brochure/Catalogue | <a href="#">CAT 3 HDC 17/18 EN</a><br><a href="#">FL FIELDWIRING EN</a> |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                |
| Engineering Data   | <a href="#">STEP</a>  |

**Data sheet**

**Crimping contact  
HDC-C-HE-SM1.5AG**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Drawings**

