

## A-series AEB 35 SC/1

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 1429-0  
Fax: +49 5231 14292083  
www.weidmueller.com



### Spring connection with **PUSH IN Technology**

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

### General ordering data

Type	AEB 35 SC/1
Order No.	<a href="#">1991920000</a>
Version	A-series, End bracket
GTIN (EAN)	4050118376722
Qty.	50 pc(s).

**A-series  
AEB 35 SC/1**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

Width	8 mm	Width (inches)	0.315 inch
Height	58 mm	Height (inches)	2.283 inch
Depth	36 mm	Depth (inches)	1.417 inch
Net weight	13.32 g		

**Temperatures**

Continuous operating temp., min.	-60 °C	Continuous operating temp., max.	130 °C
----------------------------------	--------	----------------------------------	--------

**Material data**

Material	WEMID GF 30	Colour	Dark Beige
UL 94 flammability rating	V-0		

**System specifications**

Version	For the terminals	Tightening torque (mounting screw)	1...1.2 Nm
Mounting rail	TS 35		

**Additional technical data**

Installation advice	Direct mounting	Interlock	for screw fixing
Open sides	closed	Snap-on	No
Type of mounting	Screwed	With snap-in pegs	No

**Classifications**

ETIM 6.0	EC001041	eClass 6.2	27-14-11-35
eClass 9.1	27-14-11-35		

**Approvals**

ROHS	Conform
------	---------

**Downloads**

Brochure/Catalogue	<a href="#">CAT 1 TERM 16/17 EN</a>
Engineering Data	<a href="#">EPLAN, WSCAD, Zuken E3.S</a>