

## Accessories

### SIHA 3/G20/LD 10-36V

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

### Product image



### DCS marshalling

Our innovative PRV terminal blocks for DCS marshalling featuring a PUSH IN connection and our multifunctional DCS marshalling terminals featuring a screw connection (WMF) not only save space in the panel; they also guarantee more effective signal transmission in process control systems.

### General ordering data

Type	SIHA 3/G20/LD 10-36V
Order No.	<a href="#">7921570000</a>
Version	Accessories, Fuse holder, Rated cross-section: Plug-in connection, Wemid, dark beige, Operating instructions/catalogue
GTIN (EAN)	4032248322503
Qty.	25 pc(s).

## Accessories

### SIHA 3/G20/LD 10-36V

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

Width	6 mm	Width (inches)	0.236 inch
Height	39.38 mm	Height (inches)	1.55 inch
Depth	63.1 mm	Depth (inches)	2.484 inch
Net weight	8.32 g		

### Temperatures

Operating temperature range, max.	120 °C	Operating temperature, max.	120 °C
Operating temperature, min.	-50 °C	Operating temperature	-50 °C.../TX]120 °C
Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	120 °C

### Material data

Material	Wemid	Insulating material	Wemid
Colour	Black	UL 94 flammability rating	V-0

### System specifications

Version	Fuse cartridge	End cover plate required	No
---------	----------------	--------------------------	----

### Additional technical data

Installation advice	Operating instructions/ catalogue	Type of mounting	Plugged
---------------------	--------------------------------------	------------------	---------

### Conductors for clamping (rated connection)

Type of connection	Plug-in connection
--------------------	--------------------

### Rating data

Rated voltage	250 V	Rated impulse withstand voltage	4 kV
Pollution severity	3		

### Classifications

ETIM 6.0	EC002848	ETIM 7.0	EC002848
eClass 9.0	27-14-11-92	eClass 9.1	27-14-11-92
eClass 10.0	27-14-11-92	UNSPSC	30-21-18-11

### Approvals

ROHS	Conform
------	---------

### Downloads

Brochure/Catalogue	<a href="#">CAT 1 TERM 16/17 EN</a>
Engineering Data	<a href="#">EPLAN, WSCAD, Zuken E3.S</a>
Engineering Data	<a href="#">STEP</a>
User Documentation	<a href="#">Beipackzettel_SIHA3.pdf</a> <a href="#">StorageConditionsTerminalBlocks</a>