

**Connecting elements**  
**H1,5/14D SW**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



- supplied loose in poly-bag
- Weidmüller colour code
- DIN colour code

**General ordering data**

|            |   |
|------------|---|
| Type       | H1,5/14D SW                                     |
| Order No.  | <a href="#">9019120000</a>                      |
| Version    | Wire end ferrule, insulated, 10 mm, 8 mm, Black |
| GTIN (EAN) | 4008190153793                                   |
| Qty.       | 500 pc(s).                                      |
| Packaging  | loose   |

**Data sheet**

**Connecting elements  
H1,5/14D SW**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

|            |         |                |            |
|------------|---------|----------------|------------|
| Width      | 14 mm   | Width (inches) | 0.551 inch |
| Net weight | 0.108 g |                |            |

**Technical data**

|         |           |
|---------|-----------|
| Version | insulated |
|---------|-----------|

**Wire-end ferrules**

|   |                     |                               |             |
|---|---------------------|-------------------------------|-------------|
| Collar diameter (D2)                    | 3.5 mm              | Colour code                   | DIN         |
| Conductor cross-section                 | 1.5 mm <sup>2</sup> | Contact surface diameter (D1) | 1.7 mm      |
| Contact surface length (L2)             | 8 mm                | L1 in mm                      | 14 mm       |
| Metal sleeve thickness (S1)             | 0.15 mm             | Military designation          | T 20A 012 A |
| Plastic collar thickness (S2)           | 0.25 mm             | Stripping length              | 10 mm       |
| Wire connection cross section AWG, max. | AWG 16              |                               |             |

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000005    | ETIM 4.0   | EC000005    |
| ETIM 5.0   | EC000005    | ETIM 6.0   | EC000005    |
| UNSPSC     | 31-16-31-02 | eClass 5.1 | 27-40-02-01 |
| eClass 6.2 | 27-40-02-01 | eClass 7.1 | 27-40-02-01 |
| eClass 8.1 | 27-40-02-01 | eClass 9.0 | 27-40-02-01 |
| eClass 9.1 | 27-40-02-01 |            |             |

**Approvals**

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                    |  |
|--------------------|--|
| Brochure/Catalogue | <a href="#">CAT 6 TOOLS 15/16 EN</a>     |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a> |
| Engineering Data   | <a href="#">STEP</a>                     |

**Data sheet**

**Connecting elements  
H1,5/14D SW**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

**Similar to illustration**

