

distribution terminal blocks



Conform to standard IEC 60998-2-1
 Supplied ready for use (screws captive and backed-off)
 100 A max. - 400 V \sim with 25 mm² incoming
 80 A max. - 400 V \sim with 16 mm² incoming
 Ipk (kA) 60 : Icw (kA) 3-5

Pack	Cat. Nos.	Unshrouded terminal blocks		
		Fix using M4 dia. screw		
		Incoming capacity	Outgoing capacity	Terminal length (mm)
10	0048 01	1 x 6 to 25 mm ²	4 x 1.5 to 16 mm ²	45
10	0048 03	1 x 6 to 25 mm ²	8 x 1.5 to 16 mm ²	73
10	0048 05	1 x 6 to 25 mm ²	14 x 1.5 to 16 mm ²	122
10	0048 06	1 x 6 to 25 mm ²	19 x 1.5 to 16 mm ²	157
10	0048 07	1 x 6 to 25 mm ²	24 x 1.5 to 16 mm ²	192

		Fully shrouded terminal blocks		
		Terminal blocks on support		
		Mounting on or rail with universal terminal rail support Cat. No. 0048 11 or on 12 x 2 mm rail		
		Supplied with Duplix markers ¹		
		Incoming capacity	Outgoing capacity	Terminal length (mm)
10	0048 20 ¹	-	4 x 1.5 to 16 mm ²	47
10	0048 22 ¹	-	8 x 1.5 to 16 mm ²	75
10	0048 24 ¹	1 x 6 to 25 mm ²	12 x 1.5 to 16 mm ²	113
10	0048 25 ¹	1 x 6 to 25 mm ²	16 x 1.5 to 16 mm ²	141

		IP 2X terminal blocks on support		
		For fixing to 12 x 2 mm rail		
		Incoming capacity	Outgoing capacity	Terminal length (mm)
10	Phase (black)	-	4 x 1.5 to 16 mm ²	47
10	0048 50	-	8 x 1.5 to 16 mm ²	75
10	0048 52	1 x 6 to 25 mm ²	12 x 1.5 to 16 mm ²	113
10	0048 54	1 x 6 to 25 mm ²	16 x 1.5 to 16 mm ²	141
10	0048 55	1 x 6 to 25 mm ²	21 x 1.5 to 16 mm ²	176
10	0048 56	2 x 6 to 25 mm ²	33 x 1.5 to 16 mm ²	276
10	0048 58	Neutral (blue)	-	47
10	0048 30	-	8 x 1.5 to 16 mm ²	75
10	0048 32	1 x 6 to 25 mm ²	12 x 1.5 to 16 mm ²	113
10	0048 34	1 x 6 to 25 mm ²	16 x 1.5 to 16 mm ²	141
10	0048 35	1 x 6 to 25 mm ²	21 x 1.5 to 16 mm ²	176
10	0048 36	2 x 6 to 25 mm ²	33 x 1.5 to 16 mm ²	276
10	0048 38	Earth (green)	-	47
10	0048 30	-	8 x 1.5 to 16 mm ²	75
10	0048 32	1 x 6 to 25 mm ²	12 x 1.5 to 16 mm ²	113
10	0048 34	1 x 6 to 25 mm ²	16 x 1.5 to 16 mm ²	141
10	0048 35	1 x 6 to 25 mm ²	21 x 1.5 to 16 mm ²	176
10	0048 36	2 x 6 to 25 mm ²	33 x 1.5 to 16 mm ²	276

		Supports for terminal blocks	
1	0048 10	Terminal side support	Consists of two side supports for positioning of up to 4 x IP 2X terminal blocks with the same dimensions to create a 2, 3 or 4 pole distribution block
5	0048 11	Terminal rail support	Adaptor support for or rail. Provides a firm fixing allowing IP 2X terminal blocks to be side or top mounted on to adaptor
5	0048 17	35 hole empty support	For screw terminal blocks Length : 276 mm
10	0048 19	Rail	1 metre length of 12 x 2 mm terminal mounting rail - accepts partly and fully shrouded terminals

■ Connection protection

■ Use of terminal supports Cat. No. 0048 10

Terminal supports Cat. No. 0048 10 fitted with fully shrouded terminals providing custom made distribution

Adaptor support Cat. No. 0048 11 showing method of fixing terminals

+++ Plexo weatherproof boxes p. 36-40

¹ : Each terminal supplied with :
 - 2 green Duplix markers (+) - 2 blue Duplix markers (N) - 2 red Duplix markers (L)