

Equipment for Atlantic metal cabinets (continued)



Cabinet and equipment selection chart **p. 288**
Technical characteristics **p. 295**

Pack	Cat.Nos	Cable entries for Atlantic cabinets 600 or 800 mm width
1	0 329 46	IP 43 cable entry plate with brush (cable feed-through 385 x 30 mm)
1	0 329 47	IP 55 multi-entry cable entry plate with cable glands Supplied with 12 ISO 32 cable glands The cable glands take 4 UTP/FTP/SFTP cables (Ø6.5 to 9.5 mm) per cable gland Cords with connectors can be fed through without having to dismantle the cable gland Usable interior Ø25.5 mm Supplied with blanking plates for unused entries

		Protective conductor Earth braid		
		Capacity (mm ²)	Fixing spacing (mm)	Ø of holes (mm)
20	0 347 95	6	200	8.5
20	0 347 96	16	200	8.5
10	0 347 97	30	200	8.5
		Green/yellow wire		
20	0 363 95	6	200	6.5

		Paint touch-up
1	0 365 97	Aerosol paint spray RAL 7035
10	0 365 91	Touch-up brush For protecting the sheet metal after cutting Anti-corrosion paint RAL 7035 Other colours on request

10	0 395 99	Temporary marking Water-soluble marker pen
----	----------	------------------------------------------------------

1	N 0 367 32	180° hinges RAL 7016 Enable 180° cabinet doors opening without drilling, by replacing existing hinges IP of the box maintained Kit of 2 hinges for Atlantic metal cabinets For 1-door or 2-door cabinets up to 600 mm height For 2-door cabinets order 2 kits
1	0 367 33	Kit of 3 hinges for Atlantic metal cabinets For 1-door or 2-door cabinets form 700 mm height upwards For 2-door cabinets order 2 kits

Pack	Cat.Nos	Accessories
1	N 0 367 43	Set of 4 slides for depth adjustment For 250 mm depth cabinets (starting with 600 mm width x 600 mm height cabinets)
1	0 367 44	For 300 mm depth cabinets
1	0 367 45	For 400 mm depth cabinets
1	0 364 01	Wall-mounting lugs (set of 4) For load up to 300 kg Horizontal or vertical installation With a roof, horizontal installation only Zamak RAL 7035 Supplied with cover finish
1	0 364 04	For load up to 300 kg Horizontal or vertical installation Anti-corrosion steel treatment
5	0 367 35	Attachment lugs for rail Supplied with M6 screws Set of 2 Used to attach the 15 mm depth symmetric rail on door profile strand-holder