## **C**legrand

## CAB 3<sup>™</sup> marking system

## for wiring or Viking 3 terminal blocks

0 381 51

0 381 64

N 111 11 ... ..... ишш 1*|||||||||||*||



0 381 63 mounted on Viking 3 terminal blocks



1111



0 395 05 on Viking 3 terminal blocks

0 395 20

legrand viking 3

Marking label sheets

for Viking 3 terminal blocks

0 395 98

For marking Viking 3 terminal blocks

Pack	Cat.Nos	Markers for wiring 0.5 to 1.5 mm <sup>2</sup>	Pack	Cat.Nos	Blank markers
240 240	0 381 50 0 381 51		1000 1000 1000	0 395 01	Displayed by sheet of 100 pre-cut markers Manual marking (price per marker) For blocks 5 mm pitch For blocks 6 mm pitch For blocks 8 mm pitch
240	0 381 52	21 to 40 41 to 60 61 to 80 0 381 51			Numbers
240 240 240	0 381 53 0 381 54 0 381 55	0 381 51			Correct reading direction with the marker in horizontal position. Price per marker.
240 240 240 240 240	0 381 60 0 381 61 0 381 62 0 381 63	Markers for wiring 1.5 to 2.5 mm <sup>2</sup> cross-section Strips of 20 markers (price per marker) Numbers: black on white background (available in black on yellow background on request) 01 to 20 21 to 40 41 to 60 61 to 80 81 to 100 0 381 64	1000 1000 1000 1000 1000 1000 1000	$\begin{array}{c} 0 & 395 & 05 \\ 0 & 395 & 06 \\ 0 & 395 & 07 \\ 0 & 395 & 08 \\ 0 & 395 & 09 \\ 0 & 395 & 10 \end{array}$	Pitch of 5 mm From 1 to 10 (10 times) From 11 to 20 (10 times) From 21 to 30 (10 times) From 31 to 40 (10 times) From 1 to 50 (2 times) From 1 to 100 From 101 to 200
			1000 1000 1000 1000 1000 1000 1000	0 395 16 0 395 17 0 395 18 0 395 19 0 395 20	Pitch of 6 mm From 1 to 10 (10 times) From 11 to 20 (10 times) From 21 to 30 (10 times) From 31 to 40 (10 times) From 1 to 50 (2 times) From 1 to 100 From 101 to 200

## Black felt tip pen

10 0 395 98 Indelible for marking



Same markers for cable and terminal blocks

لو

Technical characteristics p. 344

For marking wiring or Viking 3 terminal blocks

Pack	Cat.Nos	Markers for wiring 0.5 to 1.5 mm <sup>2</sup>
240 240 240 240 240 240 240	0 381 51	81 to 100 0 381 51
		Markers for wiring 1.5 to 2.5 mm <sup>2</sup> cross-section
240 240 240 240 240 240 240	0 381 61	81 to 100 0 381 64