

Colson™

installation cable ties



Dimensions **see e-catalogue**

Pack	Cat.Nos	Black Colson U.V. protected cable ties - New design																																																																		
		New design for installation with less effort Conform to EN 50146 and IEC 62275																																																																		
		External teeth New packaging offering several places to access the cable ties and hanging options (except Cat.No 0 319 21)																																																																		
		<table border="1"> <thead> <tr> <th>Width (mm)</th> <th>Flat length (mm)</th> <th colspan="2">Ø grip capacity (mm)</th> <th>Tensile Strength (kg)</th> </tr> <tr> <td></td> <td></td> <th>max.</th> <th>min.</th> <td></td> </tr> </thead> <tbody> <tr> <td>100</td> <td>0 319 10</td> <td>9</td> <td>123</td> <td>22</td> <td>4</td> <td>36</td> </tr> <tr> <td>100</td> <td>0 319 13</td> <td>9</td> <td>185</td> <td>42</td> <td>10</td> <td>36</td> </tr> <tr> <td>100</td> <td>0 319 16</td> <td>9</td> <td>262</td> <td>62</td> <td>26</td> <td>53</td> </tr> <tr> <td>100</td> <td>0 319 19</td> <td>9</td> <td>357</td> <td>92</td> <td>26</td> <td>53</td> </tr> <tr> <td>500</td> <td>0 319 20</td> <td>9</td> <td>498</td> <td>140</td> <td>74</td> <td>53</td> </tr> <tr> <td>100</td> <td>0 319 21</td> <td>9</td> <td>750</td> <td>220</td> <td>74</td> <td>53</td> </tr> <tr> <td>100</td> <td>0 319 22</td> <td>6</td> <td>119</td> <td>25</td> <td>4</td> <td>22</td> </tr> <tr> <td>1000</td> <td>0 319 25</td> <td>6</td> <td>180</td> <td>45</td> <td>10</td> <td>22</td> </tr> </tbody> </table>	Width (mm)	Flat length (mm)	Ø grip capacity (mm)		Tensile Strength (kg)			max.	min.		100	0 319 10	9	123	22	4	36	100	0 319 13	9	185	42	10	36	100	0 319 16	9	262	62	26	53	100	0 319 19	9	357	92	26	53	500	0 319 20	9	498	140	74	53	100	0 319 21	9	750	220	74	53	100	0 319 22	6	119	25	4	22	1000	0 319 25	6	180	45	10	22
Width (mm)	Flat length (mm)	Ø grip capacity (mm)		Tensile Strength (kg)																																																																
		max.	min.																																																																	
100	0 319 10	9	123	22	4	36																																																														
100	0 319 13	9	185	42	10	36																																																														
100	0 319 16	9	262	62	26	53																																																														
100	0 319 19	9	357	92	26	53																																																														
500	0 319 20	9	498	140	74	53																																																														
100	0 319 21	9	750	220	74	53																																																														
100	0 319 22	6	119	25	4	22																																																														
1000	0 319 25	6	180	45	10	22																																																														
		External teeth - large quantity boxes Reinforced boxes that can be closed again after opening Dimensions: 115 x 420 x 205 mm																																																																		
1000	2 008 11	9	185	42	10	36																																																														
650	2 008 12	9	262	62	26	53																																																														
450	2 008 13	9	357	92	26	53																																																														
		Black U.V. protected Colson cable ties																																																																		
		Internal teeth Manual tightening																																																																		
100	0 319 28	7.6	128	22	8	36																																																														
100	0 319 29	7.6	194	42	15	45																																																														
100	0 319 30	7.6	260	62	15	45																																																														
100	0 319 32	7.6	359	92	15	45																																																														
		Black U.V. protected bases																																																																		
1000	0 319 55	Standard plug base Ø8 mm drilling (Ø7 mm smooth material)																																																																		
100	0 319 58	Wall spacer plug base Ø8 mm drilling (Ø7 mm smooth material)																																																																		
100	0 319 50	Screw-on base, can be fixed with plug Cat.No 0 319 57 or metal stud Ø7 mm pitch 150 or countersunk screw Ø5 mm																																																																		

Pack	Cat.Nos	Black U.V. protected screw-in plug
100	0 319 57	For fixing screw-on base and cable ties with base Ø8 mm drilling (Ø7 mm smooth material) Threaded head Ø6.6 mm pitch 150 Supplied with punch for inserting pin
		Black cable tie with U.V. protected base Adjustable for conduits IRL Ø16 to 32 mm or for cable Ø13 to 38 mm Fixing by Ø7 mm thread 150 mm pin, screw in wall plugs Cat.No 0 319 57, screw Ø5 mm Can be fixed using Pulsa 700 E staple gun For interior and exterior use - U.V. protected Black colour
100	0 319 02	
		Colson tools Used for crimping and cutting off the excess strap close to the head of Colson cable ties
1	0 319 96	Tool for crimping and cutting the strap in 2 separate actions
1	0 319 97	Automatic tool Can be used to crimp Colson cable ties with one hand thanks to its automatic feedforward function After crimping, the surplus cable tie is automatically cut off without further action Simplifies installation and requires less effort Crimping tension can be adjusted with a thumbwheel at the end of the tool