



Main

Range	Lineryg
Product name	Lineryg DS
Product or component type	Distribution block

Complementary

Mounting support	DIN rail
Range compatibility	Prisma - G Prisma - P Prigma Prisma - PH Prisma - Pack Spacial Kaedra TeSys
Product compatibility	Spacial enclosures
Poles description	1P
Distribution block outgoers	10 holes
[Ue] rated operational voltage	230 V AC (Ph/N) 440 V AC (Ph/Ph)
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	125 A at 40 °C
[Icw] rated short-time withstand current	4.2 kA 1 s
[Ipk] rated peak withstand current	25 kA
Connections - terminals	Supply : screw terminal, 2 x 10...35 mm ² (rigid) Supply : screw terminal, 2 x 6...35 mm ² (flexible) with cable end Distribution : screw terminal, 2 x 2.5...25 mm ² (rigid) Distribution : screw terminal, 2 x 1.5...16 mm ² (flexible) with cable end Distribution : screw terminal, 6 x 1.5...16 mm ² (rigid) Distribution : screw terminal, 6 x 1.5...10 mm ² (flexible) with cable end
Tightening torque	Distribution : Ø7.5 mm, 2 N.m with flat screwdriver Distribution : Ø7.5 mm, 2 N.m with PZ2 screwdriver

Supply : Ø9.5 mm, 8 N.m with flat screwdriver
Supply : Ø9.5 mm, 8 N.m with PZ2 screwdriver
Distribution : Ø5.8 mm, 2 N.m with flat screwdriver
Distribution : Ø5.8 mm, 2 N.m with PZ2 screwdriver

9 mm pitches	3
Height	85 mm
Width	27 mm
Depth	50.5 mm
Product weight	0.127 kg
Colour	White RAL 9003

Environment

Pollution degree	3
Overvoltage category	III
Dielectric strength	2500 V
Standards	EN/IEC 60947-7-1 EN/IEC 61439-1
Ambient air temperature for operation	-25...55 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------

Contractual warranty

Warranty period	18 months
-----------------	-----------