

# Industrial Ethernet Switch - FL SWITCH 2116 - 2702908

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Managed Switch 2000, 16 RJ45 ports 10/100/1000 Mbps, degree of protection: IP20, PROFINET Conformance-Class A


The figure shows a version of the product

## Your advantages

- Suitable for PROFINET and EtherNet/IP™ networks
- Unmanaged Mode
- Easy and fast startup and commissioning with the FL NETWORK MANAGER software
- Configuration memory
- RSTP
- MRP client
- DHCP client, DHCP server (port-based)
- VLANs
- Web-based management, SNMP



## Key Commercial Data

|                                      |   |
|--------------------------------------|---|
| Packing unit                         | 1 pc  |
| GTIN                                 | <br>4 0 5 5 6 2 6 3 9 8 7 1 6 |
| GTIN                                 | 4055626398716   |
| Weight per Piece (excluding packing) | 445.000 g   |
| Custom tariff number                 | 85176200  |
| Country of origin                    | Germany   |
| Sales Key                            | DNN121  |

## Technical data

### Dimensions

|        |        |
|--------|--------|
| Width  | 85 mm  |
| Height | 130 mm |

# Industrial Ethernet Switch - FL SWITCH 2116 - 2702908

## Technical data

### Dimensions

|       |        |
|-------|--------|
| Depth | 115 mm |
|-------|--------|

### Ambient conditions

|  |   |
|--|---|
| Degree of protection                     | IP20  |
| Ambient temperature (operation)          | 0 °C ... 60 °C                              |
| Ambient temperature (storage/transport)  | -40 °C ... 85 °C                            |
| Permissible humidity (operation)         | 10 % ... 95 % (non-condensing)              |
| Permissible humidity (storage/transport) | 10 % ... 95 % (non-condensing)              |
| Air pressure (operation)                 | 86 kPa ... 108 kPa (1500 m above sea level) |
| Air pressure (storage/transport)         | 86 kPa ... 108 kPa (1500 m above sea level) |
| Degree of pollution                      | 2   |

### Interfaces

|                               |                                   |
|-------------------------------|-----------------------------------|
| Interface                     | Ethernet (RJ45)                   |
| No. of ports                  | 16 (RJ45 ports)                   |
| Note on the connection method | Auto negotiation and autocrossing |
| Transmission physics          | Copper                            |
| Transmission speed            | 10/100/1000 Mbps                  |
| Transmission length           | 100 m (per segment)               |
| Signal LEDs                   | Data receive, link status         |

### Function

|                      |  |
|----------------------|--|
| Basic functions      | Store-and-forward switch, complies with IEEE 802.3 |
| Configuration memory | max. 8 GByte (SD card)                             |
| Management           | Web-based management (HTTP/HTTPS)                  |
|                      | Role-based user management                         |
|                      | SNMPv1/v2/v3                                       |
|                      | Command-line interface (Telnet, SSH)               |
| Diagnostic functions | RMON History                                       |
|                      | LLDP (Link Layer Discovery Protocol)               |
|                      | SNMP-Traps   |
|                      | N:1-Portmirroring                                  |
|                      | ACD (Address Conflict Detection)                   |
|                      | SysLog   |
|                      | CRC-Surveillance                                   |
| Filter functions     | Quality of Service (8 priority classes)            |
|                      | Class of Service                                   |
|                      | DiffServ/DSCP                                      |
|                      | Port-Priorisierung                                 |
|                      | VLAN (up to 8 VLANs)                               |
|                      | IGMP Snooping/Querier (v1/v2)                      |
|                      | Auto-Query-Port                                    |

# Industrial Ethernet Switch - FL SWITCH 2116 - 2702908

## Technical data

### Function

|                                  |   |
|----------------------------------|---|
|                                  | Extended Multicast Filtering  |
| Redundancy                       | MRP (Media Redundancy Protocol)   |
|                                  | RSTP (Rapid Spanning Tree Protocol)   |
| Additional functions             | Jumbo frames (Max. 9,600 bytes)   |
|                                  | Transmission of MMS and GOOSE (IEC 61850-8-1)                               |
| MAC address table                | 8k  |
| IP parameterization              | DHCP-Client   |
|                                  | DHCP server (port based)  |
|                                  | BootP   |
| PROFINET conformance class       | Conformance-Class A   |
| Time synchronization             | SNTP (Simple Network Time Protocol)   |
| Status and diagnostic indicators | LEDs: US (power supply), 2 LEDs per Ethernet port (Link/Activity and Speed) |

### Network expansion parameters

|   |  |
|---|--|
| Cascading depth                         | Network, linear, and star structure: any |
| Maximum conductor length (twisted pair) | 100 m                                    |

### Supply voltage

|                             |  |
|-----------------------------|--|
| Supply voltage              | 24 V DC (single)   |
| Residual ripple             | 3.6 V <sub>pp</sub> (within the permitted voltage range)           |
| Supply voltage range        | 18 V DC ... 32 V DC  |
| Typical current consumption | 315 mA (at U <sub>S</sub> = 24 V DC and 25 °C ambient temperature) |
| Max. current consumption    | 0.7 A (At U <sub>S</sub> = 18 V DC and 60°C ambient temperature)   |
| Current consumption         | 455 mA   |

### General

|                  |  |
|------------------|--|
| Mounting type    | DIN rail   |
| Type AX          | Book type  |
| Net weight       | 445 g  |
| Housing material | Polycarbonate fiber reinforced   |
| Note             | Support by phone or on-site (fee is charged)                               |
| MTTF             | 379.84 Years (SN 29500 standard, temperature 25°C, operating cycle 21%)    |
|                  | 199.41 Years (SN 29500 standard, temperature 40°C, operating cycle 34.25%) |
|                  | 40.42 Years (SN 29500 standard, temperature 55°C, operating cycle 100%)    |

### Connection data

|                                       |                           |
|---------------------------------------|---------------------------|
| Connection method                     | Push-in spring connection |
| Conductor cross section solid min.    | 0.25 mm <sup>2</sup>      |
| Conductor cross section solid max.    | 1.5 mm <sup>2</sup>       |
| Conductor cross section flexible min. | 0.25 mm <sup>2</sup>      |

# Industrial Ethernet Switch - FL SWITCH 2116 - 2702908

## Technical data

### Connection data

|                                       |                     |
|---------------------------------------|---------------------|
| Conductor cross section flexible max. | 1.5 mm <sup>2</sup> |
| Conductor cross section AWG min.      | 24                  |
| Conductor cross section AWG max.      | 16                  |
| Stripping length                      | 9 mm                |

### Standards and Regulations

|   |   |
|---|---|
| Electromagnetic compatibility                                     | Conformance with EMC Directive 2014/30/EU                         |
| Interference emission   | EN 61000-6-2 EN 61000-6-3 (noise emission) Class B                |
| Conducted noise emission  | EN 61000-6-2 EN 61000-6-3 (conducted emissions) Class B           |
| Immunity to surge   | EN 61000-6-2 EN 61000-4-5 (surge) Criterion B                     |
| Immunity to burst   | EN 61000-6-2 EN 61000-4-4 (EFT burst) Criterion A                 |
| Immunity to EF  | EN 61000-6-2 EN 61000-4-3 (electromagnetic fields) Criterion A    |
| Immunity to ESD   | EN 61000-6-2 EN 61000-4-2 (ESD) Criterion B                       |
| Immunity to conducted interference                                | EN 61000-6-2 EN 61000-4-6 (line noise immunity) Criterion A       |
| Type of test  | Free fall in accordance with EN 61131-2                           |
| Noise emission  | EN 61000-6-4  |
| Noise immunity  | EN 61000-6-2  |
| Vibration (storage/transport)                                     | 2g, criterion 1 according to IEC 60068-2-6                        |
| Free from substances that could impair the application of coating | Yes   |
| Vibration (operation)   | 2g, according to IEC 60068-2-6                                    |
| Shock (operation)   | 30g (EN 60068-2-27)   |
| UL, USA   | UL 61010-1, Ed.3 / UL 61010-2-201, Ed.1                           |
| UL, Canada  | CSA C22.2 NO.61010-2-201:14, Ed.1 / CSA C22.2 NO.61010-1-12, Ed.3 |

### Environmental Product Compliance

|            |   |
|------------|---|
| REACH SVHC | Lead 7439-92-1  |
| China RoHS | Environmentally Friendly Use Period = 50 years  |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Classifications

### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 19170401 |
| eCl@ss 11.0   | 19170401 |
| eCl@ss 4.0    | 27250501 |
| eCl@ss 4.1    | 27250501 |
| eCl@ss 5.0    | 19030100 |
| eCl@ss 5.1    | 19030100 |
| eCl@ss 6.0    | 19170100 |
| eCl@ss 7.0    | 19170106 |

# Industrial Ethernet Switch - FL SWITCH 2116 - 2702908

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 9.0 | 19170106 |
|------------|----------|

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000734 |
| ETIM 4.0 | EC000734 |
| ETIM 5.0 | EC000734 |
| ETIM 6.0 | EC000734 |
| ETIM 7.0 | EC000734 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11     | 43172015 |
| UNSPSC 12.01  | 43201410 |
| UNSPSC 13.2   | 43201410 |
| UNSPSC 18.0   | 43222612 |
| UNSPSC 19.0   | 43222612 |
| UNSPSC 20.0   | 43222612 |
| UNSPSC 21.0   | 43222612 |

## Approvals

### Approvals

#### Approvals

UL Listed / cUL Listed / EAC / BSH / CC-Link IE Field / cULus Listed

#### Ex Approvals

### Approval details

|           |   |   |               |
|-----------|---|---|---------------|
| UL Listed |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 238705 |
|-----------|---|---|---------------|

|            |   |   |               |
|------------|---|---|---------------|
| cUL Listed |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 238705 |
|------------|---|---|---------------|

# Industrial Ethernet Switch - FL SWITCH 2116 - 2702908

## Approvals

|     |  |                          |
|-----|--|--------------------------|
| EAC |  | RU* -<br>DE.*.B.00741/19 |
|-----|--|--------------------------|

|     |      |
|-----|------|
| BSH | 1045 |
|-----|------|

|                  |  |              |
|------------------|--|--------------|
| CC-Link IE Field |  | Ref. No. 184 |
|------------------|--|--------------|

|              |  |
|--------------|--|
| cULus Listed |  |
|--------------|--|

## Accessories

### Accessories

#### Data cable preassembled

Patch cable - NBC-R4AC-R4AC-IE8A/.../... - 1411854



Patch cable, degree of protection: IP20, number of positions: 8, 10 Gbps, CAT6<sub>A</sub>, cable outlet: straight, Ethernet

Patch cable - NBC-R4AC/10G-R4AC/10G-94F/2,0 - 1408360



Patch cable, CAT6<sub>A</sub>, 4-pair, shielded, connection not crossed (line), assembled at both ends with RJ45/IP20 connectors, outer sheath material: PUR, length: 2.0 m

Patch cable - NBC-R4AC/10G-R4AC/10G-94F/3,0 - 1408365



Patch cable, CAT6<sub>A</sub>, 4-pair, shielded, connection not crossed (line), assembled at both ends with RJ45/IP20 connectors, outer sheath material: PUR, length: 3.0 m

## Industrial Ethernet Switch - FL SWITCH 2116 - 2702908

### Accessories

Patch cable - NBC-R4AC/1,0-93B/R4AC - 1408968



Patch cable, degree of protection: IP20, cable length: 1 m, number of positions: 4, 100 Mbps, CAT5, material: PA 6.6, PROFINET

---

Patch cable - NBC-R4AC/2,0-93B/R4AC - 1408969



Patch cable, degree of protection: IP20, cable length: 2 m, number of positions: 4, 100 Mbps, CAT5, material: PA 6.6, PROFINET

---

Patch cable - NBC-R4AC/5,0-93B/R4AC - 1408970



Patch cable, degree of protection: IP20, cable length: 5 m, number of positions: 4, 100 Mbps, CAT5, material: PA 6.6, PROFINET

---

### Drivers and interfaces

Software - FL SNMP OPC SERVER V3 - 2701139



SNMP-OPC server, German and English, for monitoring and configuration of SNMP-capable equipment in HMI and SCADA systems

---

### End block

End clamp - E/NS 35 N - 0800886



End clamp, width: 9.5 mm, color: gray

---

### Mounting rail adapter

# Industrial Ethernet Switch - FL SWITCH 2116 - 2702908

## Accessories

DIN rail adapter - FL DIN RA - 2891053



The FL DIN RA is installed in a standard, 19-inch rack (EIA-310-D, IEC 60297-3-100) to allow DIN rail mounted equipment to be rack mounted.

---

## Network management software

Software - FL NETWORK MANAGER BASIC - 2702889



FL Network Manager, SNMP-based configuration and firmware update software, for easy startup of Managed Switches

---

## Parameterization memory

Memory - SD FLASH 512MB - 2988146



Program and configuration memory, plug-in, 512 Mbyte.

---

Program / configuration memory - SD FLASH 2GB - 2988162



Program and configuration memory, for extending the internal flash memory, pluggable, 2 GB.

---

## Patch cable

Patch cable - FL CAT5 PATCH 0,5 - 2832263



Patch cable, CAT5, assembled, 0.5 m



# Industrial Ethernet Switch - FL SWITCH 2116 - 2702908

## Accessories

Patch cable - FL CAT5 PATCH 1,0 - 2832276



Patch cable, CAT5, assembled, 1 m

Patch cable - FL CAT5 PATCH 2,0 - 2832289



Patch cable, CAT5, assembled, 2 m

## PCB plug

Printed-circuit board connector - FK-MCP 1,5/ 5-ST-3,81GY35BD1-5 - 1015782



PCB connector, nominal cross section: 1.5 mm<sup>2</sup>, color: light gray, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Tin, type of contact: Female connector, Number of potentials: 5, Number of rows: 1, Number of positions per row: 5, number of connections: 5, product range: FK-MCP 1,5/..-ST, pitch: 3.81 mm, connection method: Push-in spring connection, conductor/PCB connection direction: 0 °, plug-in system: MINI COMBICON, Locking: without, type of packaging: packed in cardboard

PCB connector - MCVW 1,5/ 5-ST-3,81GY7035BD2US - 1034103



PCB connector, nominal cross section: 1.5 mm<sup>2</sup>, color: light gray, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Tin, type of contact: Female connector, Number of potentials: 5, Number of rows: 1, Number of positions per row: 5, number of connections: 5, product range: MCVW 1,5/..-ST, pitch: 3.81 mm, connection method: Screw connection with tension sleeve, conductor/PCB connection direction: -90 °, plug-in system: MINI COMBICON, Locking: without, type of packaging: packed in cardboard

## Protective cap

Dust protection - FL RJ45 PROTECT CAP - 2832991



Dust protection caps for RJ45 socket