

Plug-in bridge - FBS 20-5 - 3030226

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Plug-in bridge, pitch: 5.2 mm, number of positions: 20, color: red

Why buy this product

The 2- to 50-pos. jumpers can bridge up to 50 terminal blocks in the two bridge shafts of the CLIPLINE complete system in one step



Key Commercial Data

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	4 017918 188559
GTIN	4017918188559
Weight per Piece (excluding packing)	17.000 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

Technical data

Color	red
Material	Copper
Number of positions	20
Pitch	5.2 mm
Flammability rating according to UL 94	V0
Maximum load current	24 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)

Standards and Regulations

Flammability rating according to UL 94	V0

Environmental Product Compliance



Plug-in bridge - FBS 20-5 - 3030226

Technical data

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC

EHE

EAC-Zulassung

Accessories

Accessories

Cutting tools

Front cutter - CUTFOX-FBS - 1212124



 $Cutting \ tool, for \ separating \ individual \ jumper \ bars \ from \ FBS \ ... \ plug-in \ bridges \ and \ EB \ ... \ insertion \ bridges$

Protective cap

Protective cap - FBSC - 3012325



Covering hood, provides reliable shock protection when using cut-to-length FBS ...-5 and FBS ...-6 bridges, color: red



Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com