

Plug-in bridge - FBS 10-6 - 3030271

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Plug-in bridge, pitch: 6.2 mm, width: 60.3 mm, number of positions: 10, color: red



Why buy this product

The 2- to 50-pos. jumpers can bridge up to 50 terminal blocks in the two bridge shafts of the CLIPLINE complete system in one step



Key Commercial Data

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	4 017918 188580
GTIN	4017918188580
Weight per Piece (excluding packing)	9.700 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

Technical data

Color	red
Material	Copper
Number of positions	10
Pitch	6.2 mm
Height	23 mm
Width	60.3 mm
Flammability rating according to UL 94	V0
Maximum load current	32 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)

Standards and Regulations



Plug-in bridge - FBS 10-6 - 3030271

Technical data

Standards and Regulations

Flammability rating according to UL 94	V0
Environmental Product Compliance	

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC	EAC	EAC-Zulassung
Accessories		

Accessories

Cutting tools

Front cutter - CUTFOX-FBS - 1212124



Cutting tool, for separating individual jumper bars from FBS ... plug-in bridges and EB ... insertion bridges

Protective cap

Protective cap - FBSC - 3012325



Covering hood, provides reliable shock protection when using cut-to-length FBS ...-5 and FBS ...-6 bridges, color: red



Plug-in bridge - FBS 10-6 - 3030271

Accessories

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com