Rittal - The System.

Faster – better – everywhere.

Compact enclosure AX Basic enclosure AX, stainless steel – AX 1005.000

Date: Jan 22, 2020



Compact enclosure AX Basic enclosure AX, stainless steel – AX 1005.000

created: 22.01.2020 build on www.rittal.com/uk-en



_			
Prod	luct	desc	ription

Material: Enclosure: Stainless steel

Door: Stainless steel, all-round foamed-in PU seal

Mounting plate: Sheet steel

Lock: Die-cast zinc, nickel-plated, double-bit insert stainless steel

Stainless steel 1.4301 (AISI 304)

Surface finish: Enclosure and door: Brushed, grain 400, peak-to-valley height < 0.8 μm

Mounting plate: Zinc-plated

Protection category IP to IEC 60 529:

IP 66

Protection category NEMA:

NEMA 4X

Type rating to UL

508A:

Type 3X/4X

IK Code:

IK08

Supply includes: Enclosure with door(s), opening angle 130°

Mounting plate

Lock: 3 mm double-bit

Basic material: Stainless steel 1.4301 (AISI 304)

Product features

Dimensions: Width: 300 mm

Height: 380 mm Depth: 210 mm

© Rittal 2020

1

Mounting plate:	Width: 250 mm Height: 355 mm		
Number of doors:	1		
Number of cam locks:	1		
Lock version:	Cam		
Number of locks:	1		
Lock insert:	3 mm double-bit		
Packs of:	1 pc(s).		
Weight/pack:	8.4 kg		
EAN:	4028177814943		
Customs tariff number:	94032080		
ETIM 7.0:	EC000261		
ETIM 6.0:	EC000261		
e CI@ss 8.0/8.1:	27180101		
e CI@ss 6.0/6.1:	27180101		
Product description:	AX Compact enclosure, WHD: 300x380x210 mm, stainless steel 1.4301, with mounting plate, single-door, with one cam lock		

© Rittal 2020 2