Rittal - The System.

Faster – better – everywhere.

Compact enclosure
AX Basic enclosure
AX, stainless steel –
AX 1012.000

Date: Jan 22, 2020



Compact enclosure AX Basic enclosure AX, stainless steel – AX 1012.000

created: 22.01.2020 build on www.rittal.com/uk-en



		_	_	
Prod	uct	des	crin	tion

Material: Enclosure: Stainless steel

Door: Stainless steel, all-round foamed-in PU seal

Mounting plate: Sheet steel

Lock: Die-cast zinc, nickel-plated, double-bit insert stainless steel

Stainless steel 1.4301 (AISI 304)

Surface finish: Enclosure and door: Brushed, grain 400, peak-to-valley height < 0.8 µm

Mounting plate: Zinc-plated

Protection category IP to IEC 60 529:

IP 66

Protection category NEMA:

NEMA 4X

Type rating to UL

508A:

Type 3X/4X

IK Code:

IK08

Supply includes: Enclosure with door(s), opening angle 130°

Mounting plate

Lock: 3 mm double-bit

Basic material: Stai

Stainless steel 1.4301 (AISI 304)

Product features

Dimensions: Width: 600 mm

Height: 760 mm Depth: 210 mm

© Rittal 2020

1

Mounting plate:	Width: 550 mm Height: 735 mm		
Number of doors:	1		
Number of cam locks:	2		
Lock version:	Cam		
Number of locks:	2		
Lock insert:	3 mm double-bit		
Packs of:	1 pc(s).		
Weight/pack:	30.2 kg		
EAN:	4028177815001		
Customs tariff number:	94032080		
ETIM 7.0:	EC000261		
ETIM 6.0:	EC000261		
e Cl@ss 8.0/8.1:	27180101		
e Cl@ss 6.0/6.1:	27180101		
Product description:	AX Compact enclosure, WHD: 600x760x210 mm, stainless steel 1.4301, with mounting plate, single-door, with two cam locks		

© Rittal 2020 2