Rittal - The System.

Faster – better – everywhere.

Compact enclosure AX Basic enclosure AX, sheet steel – AX 1057.000

Date: Feb 13, 2020



Compact enclosure AX Basic enclosure AX, sheet steel – AX 1057.000

created: 13.02.2020 build on www.rittal.com/uk-en



Product description	
Material:	Enclosure: Sheet steel Door: Sheet steel, all-round foamed-in PU seal
Surface finish:	Enclosure and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Type rating to UL 508A:	Type 3R/4
Supply includes:	Enclosure with door(s) Gland plate(s) in enclosure base Mounting plate Perforated door strip Lock: 3 mm double-bit
Basic material:	Sheet steel
Product features	
Dimensions:	Width: 500 mm Height: 700 mm Depth: 250 mm

© Rittal 2020

Material thickness: Enclosure: 1.5 mm Door: 2 mm Mounting plate: 2.5 mm Width: 450 mm Mounting plate: Height: 675 mm Number of doors: 1 Door hinged on the yes right, may be swapped to the left: 2 Number of cam locks: Lock version: Cam **Number of locks:** 2 Lock insert: 3 mm double-bit 3 Gland plate, size: Gland plate, qty.: 1 Packs of: 1 pc(s). Weight/pack: 25 kg EAN: 4028177813335 **Customs tariff** 94032080 number: ETIM 7.0: EC000261 ETIM 6.0: EC000261 27180101 eCl@ss 8.0/8.1: eCl@ss 6.0/6.1: 27180101 **Product description:** AX Compact enclosure, WHD: 500x700x250 mm, sheet steel, with mounting plate, single-door, with two cam locks

Approvals

Approvals: UL + C-UL

Declarations: Declaration of conformity

© Rittal 2020

3