

# Rittal – The System.

Faster – better – everywhere.

## ► Compact enclosure AX Basic enclosure AX, stainless steel – AX 1303.000

Date : Jan 20, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Compact enclosure AX Basic enclosure AX, stainless steel – AX 1303.000

created: 20.01.2020 build on [www.rittal.com/uk-en](http://www.rittal.com/uk-en)



## Product description

<b>Material:</b>	Enclosure: Stainless steel Door: Stainless steel, all-round foamed-in PU seal Mounting plate: Sheet steel Lock: Die-cast zinc, nickel-plated, double-bit insert stainless steel Stainless steel 1.4404 (AISI 316L)
<b>Surface finish:</b>	Enclosure and door: Brushed, grain 400, peak-to-valley height < 0.8 µm Mounting plate: Zinc-plated
<b>Protection category IP to IEC 60 529:</b>	IP 66
<b>Protection category NEMA:</b>	NEMA 4X
<b>Type rating to UL 508A:</b>	Type 3X/4X
<b>IK Code:</b>	IK08
<b>Supply includes:</b>	Enclosure with door(s), opening angle 130° Mounting plate Lock: 3 mm double-bit
<b>Basic material:</b>	Stainless steel 1.4404 (AISI 316L)

## Product features

<b>Dimensions:</b>	Width: 380 mm Height: 380 mm Depth: 210 mm
--------------------	--------------------------------------------------

<b>Mounting plate:</b>	Width: 330 mm Height: 355 mm
<b>Number of doors:</b>	1
<b>Number of cam locks:</b>	1
<b>Lock version:</b>	Cam
<b>Number of locks:</b>	1
<b>Lock insert:</b>	3 mm double-bit
<b>Packs of:</b>	1 pc(s).
<b>Weight/pack:</b>	9.8 kg
<b>EAN:</b>	4028177815087
<b>Customs tariff number:</b>	94032080
<b>ETIM 7.0:</b>	EC000261
<b>ETIM 6.0:</b>	EC000261
<b>eCl@ss 8.0/8.1:</b>	27180101
<b>eCl@ss 6.0/6.1:</b>	27180101
<b>Product description:</b>	AX Compact enclosure, WHD: 380x380x210 mm, stainless steel 1.4404, with mounting plate, single-door, with one cam lock