

Rittal – The System.

Faster – better – everywhere.

► Small enclosures KX E-Box KX, sheet steel – KX 1551.000

Date : Mar 27, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Small enclosures KX E-Box KX, sheet steel – KX 1551.000

created: 27.03.2020 build on www.rittal.com/uk-en



Product description

Description:	The small enclosure KX, E-Box KX (sheet steel), offers remarkable ease of assembly and flexibility when selecting lock systems.
Material:	Enclosure: Sheet steel Door: Sheet steel, all-round foamed-in PU seal
Surface finish:	Enclosure and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Type rating to UL 508A:	Type 3R/4
IK Code:	IK08
Supply includes:	Enclosure with door Mounting plate Cam lock with 3 mm double-bit insert
Basic material:	Sheet steel

Product features

Dimensions:	Width: 150 mm Height: 150 mm Depth: 80 mm
Outlet direction:	The small enclosure KX, E-Box KX (sheet steel), offers remarkable ease of assembly and flexibility when selecting lock systems.
Material thickness:	Enclosure: 1.25 mm Door: 1.25 mm Mounting plate: 2 mm
Mounting plate:	Width: 125 mm Height: 135 mm
Packs of:	1 pc(s).
Weight/pack:	1.49 kg
EAN:	4028177816534
Customs tariff number:	94032080
ETIM 7.0:	EC002713
ETIM 6.0:	EC002713
eCl@ss 8.0/8.1:	27180101
eCl@ss 6.0/6.1:	27180101
Product description:	KX E-Box, WHD: 150x150x80 mm, sheet steel, with mounting plate, with door
Approvals	
Approvals:	UL + C-UL
Declarations:	Declaration of conformity