

Rittal – The System.

Faster – better – everywhere.

► Bus enclosures BG Stainless steel – BG 1559.010

Date : Jul 26, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Bus enclosures BG Stainless steel – BG 1559.010

created: 26.07.2017 build on www.rittal.com/uk-en



Product description

Material: Enclosure: Stainless steel 1.4301 (AISI 304)
Cover: Stainless steel 1.4301 (AISI 304), all-round foamed-in PU seal
180° hinges: Die-cast zinc

Surface finish: Enclosure and cover: Brushed, grain 240
180° hinges: chrome-plated

**Protection category
IP to IEC 60 529:** IP 66

**Protection category
NEMA:** NEMA 4X

Supply includes: Enclosure with cover
180° hinges (2)
Support rail TS 35/7.5
Quick-release fastener including plastic bushes

Basic material: Stainless steel

Product features

Dimensions: Width: 600 mm
Height: 200 mm
Depth: 123 mm

Support rails: Qty. (type TS 35/7.5): 1

Design support rail: adjustable on profile strip

Material thickness: Enclosure: 1.5 mm

Door: 1.25 mm

Door hinge:	bottom
Lock version:	Quick-release fastener including plastic bushes
Number of locks:	3
Packs of:	1 pc(s).
Weight/pack:	6 kg
EAN:	4028177009950
Customs tariff number:	94032080
ETIM 6.0:	EC002713
ETIM 5.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180103
Product description (long):	BG Bus enclosure, WHD: 600x200x123 mm, Stainless steel 1.4301, without mounting plate, with cover, with support rail
Approvals	
Approvals:	Lloyds Register of Shipping NA TÜV UL + C-UL
Certificates:	EAC Protection category
Declarations:	Declaration of conformity