Rittal - The System.

Faster – better – everywhere.

Small enclosures KX E-Box KX, stainless steel – KX 1584.000

Date: Feb 4, 2020



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Small enclosures KX E-Box KX, stainless steel – KX 1584.000

created: 04.02.2020 build on www.rittal.com/uk-en



Product description	
Description:	The small enclosure KX, E-Box KX (stainless steel), offers remarkable ease of assembly and flexibility when selecting lock systems. The series-standard 180° hinges provide easy access to the enclosure interior.
Material:	Enclosure: Stainless steel Door: Stainless steel, all-round foamed-in PU seal Mounting plate: Sheet steel Stainless steel 1.4301 (AISI 304)
Surface finish:	Enclosure and door: Brushed, grain 400, peak-to-valley height < 0.8 µm Mounting plate: Zinc-plated
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4X
Type rating to UL 508A:	Type 3X/4X
Supply includes:	Mounting plate Cam lock with 3 mm double-bit insert
Basic material:	Stainless steel 1.4301 (AISI 304)
Product features	
Dimensions:	Width: 200 mm

© Rittal 2020

Height: 300 mm Depth: 120 mm

Material thickness:	Enclosure: 1.25 mm Door: 1.25 mm
Mounting plate:	Width: 175 mm Height: 285 mm
Packs of:	1 pc(s).
Weight/pack:	3.6 kg
EAN:	4028177919105
Customs tariff number:	94032080
ETIM 7.0:	EC002713
ETIM 6.0:	EC002713
eCl@ss 8.0/8.1:	27180101
eCl@ss 6.0/6.1:	27180101
Product description:	KX E-Box, WHD: 200x300x120 mm, stainless steel 1.4301, with mounting plate, single-door, with one cam lock

© Rittal 2020