

Rittal – The System.

Faster – better – everywhere.

► Small enclosures KX Bus enclosures KX, stainless steel – KX 1585.000

Date : Feb 4, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Small enclosures KX Bus enclosures KX, stainless steel – KX 1585.000

created: 04.02.2020 build on www.rittal.com/uk-en



Product description

Description: The small enclosure KX, bus enclosure KX (sheet steel), allows for flexible interior installation and provides easy access thanks to the series-standard 180° hinges.

Material: Enclosure: Stainless steel 1.4301 (AISI 304)
Cover: Stainless steel 1.4301 (AISI 304), all-round foamed-in PU seal
Hinges: Die-cast zinc

Surface finish: Enclosure and cover: Brushed, grain 400, peak-to-valley height < 0.8 µm

Protection category IP to IEC 60 529: IP 66

Protection category NEMA: NEMA 4X

Type rating to UL 508A: Type 3X/4X

Supply includes: Enclosure with hinged cover
Mini cam locks

Basic material: Stainless steel 1.4301 (AISI 304)

Product features

Dimensions: Width: 400 mm
Height: 200 mm
Depth: 120 mm

Design support rail: attached to studs

Material thickness:	Enclosure: 1.25 mm Door: 1.25 mm
Door hinge:	right/left
Weight/pack:	4.5 kg
ETIM 7.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 6.0/6.1:	27180101
Product description:	KX Bus enclosure, WHD: 400x200x120 mm, stainless steel 1.4301, with hinged lid