

Rittal – The System.

Faster – better – everywhere.

► Small enclosures KX E-Box KX, stainless steel – KX 1587.000

Date : Jan 24, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Small enclosures KX E-Box KX, stainless steel – KX 1587.000

created: 24.01.2020 build on www.rittal.com/uk-en



Product description

Description:	The small enclosure KX, E-Box KX (stainless steel), offers remarkable ease of assembly and flexibility when selecting lock systems. The series-standard 180° hinges provide easy access to the enclosure interior.
Material:	Enclosure: Stainless steel Door: Stainless steel, all-round foamed-in PU seal Mounting plate: Sheet steel Stainless steel 1.4301 (AISI 304)
Surface finish:	Enclosure and door: Brushed, grain 400, peak-to-valley height < 0.8 µm Mounting plate: Zinc-plated
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4X
Type rating to UL 508A:	Type 3X/4X
Supply includes:	Mounting plate Cam lock with 3 mm double-bit insert
Basic material:	Stainless steel 1.4301 (AISI 304)

Product features

Dimensions:	Width: 200 mm Height: 300 mm Depth: 155 mm
--------------------	--

Material thickness:	Enclosure: 1.25 mm Door: 1.25 mm
Mounting plate:	Width: 175 mm Height: 285 mm
Packs of:	1 pc(s).
Weight/pack:	4.1 kg
EAN:	4028177919136
Customs tariff number:	94032080
ETIM 7.0:	EC002713
ETIM 6.0:	EC002713
eCl@ss 8.0/8.1:	27180101
eCl@ss 6.0/6.1:	27180101
Product description:	KXE-Box, WHD: 200x300x155 mm, stainless steel 1.4301, with mounting plate, single-door, with one cam lock