

Rittal – The System.

Faster – better – everywhere.

Captive nuts – EL 2092.200

Date : Nov 16, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Captive nuts – EL 2092.200

created: 16.11.2019 build on www.rittal.com/uk-en



Product description

Design: Without contact

Description: For the attachment of rack-mounted electronic equipment, 482.6 mm (19") installed equipment and blanking plates to mounting angles, 482.6 mm (19"). For use with metal thickness from 0.8 – 2.0 mm. In areas of narrow tolerance, captive nuts for metal thicknesses of 1.2 – 1.5 mm should be used. Optionally with or without contact of the installed equipment to the 482.6 mm (19") section/enclosure.

Product features

Thread: Type: M6

For metal thicknesses: 0,8 mm - 2 mm

Packs of: 50 pc(s).

Weight/pack: 0.2 kg

Copper weight (kg per piece): 0

EAN: 4028177014114

Customs tariff number: 73181692

ETIM 7.0: EC002358

ETIM 6.0: EC002358

eCl@ss 8.0/8.1: 23110815

eCl@ss 6.0/6.1: 27182590

Product description: EL Captive nuts, M6, Without contact, For metal thickness: 0,8-2 mm
