

Rittal – The System.

Faster – better – everywhere.

► Incandescent lamps for steady light components – SG 2374.060

Date : Dec 6, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Incandescent lamps for steady light components – SG 2374.060

created: 06.12.2017 build on www.rittal.com/uk-en



Product description

Description:	With BA 15d base.
Benefits:	Simple assembly and contact via bayonet fastener.
Function principle:	A modular layout is possible with connection, optical and acoustic components, incandescent lamps and a label panel.

Product features

Rated operating voltage:	24 V
Power consumption:	5 W
Rated insulation voltage:	2000 V AC
Rated impulse withstand voltage, phase to phase:	28 V AC
Packs of:	3 pc(s).
Weight/pack:	0.03 kg
EAN:	4028177219885
Customs tariff number:	85392198

ETIM 6.0:	EC000232
ETIM 5.0:	EC000232
eCl@ss 8.0/8.1:	27371220
eCl@ss 7.0/7.1:	27371220
eCl@ss 6.0/6.1:	27371220
eCl@ss 5.1/5.1.4:	27371220
Product description (long):	SG Incandescent lamp, for steady light component, 24 V, 5W
Approvals	
Certificates:	EAC