Rittal - The System.

Faster – better – everywhere.

Enclosure heaters without fan – SK 3105.370

Date: Jan 17, 2017



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Enclosure heaters without fan - SK 3105.370

created: 17.01.2017 build on www.rittal.com/uk-en



Prod	luct d	desci	ription
1 100	uct	1 0 301	ipuon

Supply includes: PTC heater

Quick-connection terminal

Assembly parts

Note: For precise temperature control inside the enclosure, we recommend the enclosure internal

thermostat or the digital enclosure internal temperature display and thermostat.

In order to prevent condensation on assemblies, a hygrostat is recommended to regulate

heating.

In larger enclosures, even heat distribution is best achieved by installing several low-output

heaters

The installation of heaters is generally advisable, in order to prevent condensation.

Note on Model No.: Special voltages available on request. We reserve the right to make technical modifications.

Product features

Continuous thermal output at 10°C:

130 W - 150 W

Rated operating voltage:

110 V - 240 V, 1~, 50 Hz/60 Hz

Dimensions:

Width: 90 mm Height: 180 mm Depth: 75 mm

Pre-fuse: Miniature circuit-breaker/fuse: 4 A

Packs of: 1 pc(s).

Weight/pack: 0.9 kg

© Rittal 2017

EAN:	4028177638679
Customs tariff number:	85162999
ETIM 6.0:	EC000737
ETIM 5.0:	EC000737
eCl@ss 8.0/8.1:	27180710
eCl@ss 7.0/7.1:	27180710
eCl@ss 6.0/6.1:	27180710
eCl@ss 5.1/5.1.4:	27180710
Approvals	
Approvals:	Approval overview C-UR CSA UR UR VDE
Declarations:	Declaration of conformity

2017 © Rittal Ltd UK

© Rittal 2017