

# Rittal – The System.

Faster – better – everywhere.

## ► Enclosure internal fan for VX, TS – SK 3108.100

Date : Apr 30, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Enclosure internal fan for VX, TS – SK 3108.100

created: 30.04.2019 build on [www.rittal.com/uk-en](http://www.rittal.com/uk-en)



## Product description

**Description:** To prevent hot-spots and support the air routing of active enclosure climate control components. Adjustable in two axes. Attached to the frame section. Several fans may be cascaded using the quick-release clamping strip.

**Supply includes:** Complete unit with radial fan ready for connection  
Snap-on pivot device  
Assembly parts

## Product features

**Air throughput (unimpeded air flow):** 160 m<sup>3</sup>/h

**Air throughput, unimpeded air flow (without filter mats):**

**Air throughput, unimpeded air flow (with filter mats):**

**Rated operating voltage:** 230 V, 1~, 50 Hz/60 Hz

**Power consumption P<sub>sub-el-subcl</sub>:** At 50 Hz: 19 W  
At 60 Hz: 18 W

**Rated current (max.):** At 50 Hz: 0.12 A  
At 60 Hz: 0.11 A

**Packs of:** 1 pc(s).

**Weight/pack:** 1.14 kg

<b>EAN:</b>	4028177220485
<b>Customs tariff number:</b>	84145915
<b>ETIM 6.0:</b>	EC000320
<b>ETIM 5.0:</b>	EC000320
<b>eCl@ss 8.0/8.1:</b>	27180716
<b>eCl@ss 7.0/7.1:</b>	27180716
<b>eCl@ss 6.0/6.1:</b>	27180716
<b>eCl@ss 5.1/5.1.4:</b>	27180705
<b>Product description:</b>	SK enclosure internal fan, 19/18 W, 230 V, 1~, 50/60 Hz
<b>Approvals</b>	
<b>Approvals:</b>	Approval overview
<b>Certificates:</b>	EAC
<b>Declarations:</b>	Declaration of conformity