

Rittal – The System.

Faster – better – everywhere.

Hygrostat – SK 3118.000

Date : Oct 17, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Hygrostat – SK 3118.000

created: 17.10.2019 build on www.rittal.com/uk-en



Product description

Description: Activates the heater and/or fan when a preset relative humidity in the enclosure is exceeded. This reduces the relative humidity and prevents condensation on assemblies and electronic components.

Benefits: Time-saving connection technique using a terminal strip with a screw connection from the outside.
Flexible mounting on a vertical or horizontal 35 mm support rail to EN 50 022, and snap fastening in the enclosure section or on the mounting plate using the supplied adaptor

Technical specifications: Contact population: Single-pole change-over contact as a quick-break contact
Permissible contact load: AC ~ 5 (0.2) A (inductive load at $\cos \varphi = 0.6$)/DC = max. 20 W
Setting range: 50 – 100% relative humidity
Switching difference: approx. 4%

Colour: RAL 7035

Product features

Rated operating voltage: 24 V - 250 V, 1~
24 V - 75 V (DC)

Dimensions: Width: 71 mm
Height: 71 mm
Depth: 33.5 mm

Packs of: 1 pc(s).

Weight/pack: 0.1 kg

EAN: 4028177036734

Customs tariff number:	90321080
ETIM 6.0:	EC002008
ETIM 5.0:	EC002008
eCl@ss 8.0/8.1:	27210708
eCl@ss 7.0/7.1:	27210708
eCl@ss 6.0/6.1:	27210708
eCl@ss 5.1/5.1.4:	27180792
Product description:	SK Hygrostat, 24-230 V, 1~, 12-75 V (DC), Colour RAL 7035, WHD: 71 x 71 x 33.5 mm
Approvals	
Approvals:	CCC exception letter
Certificates:	EAC