

Rittal – The System.

Faster – better – everywhere.

► Speed control For fan- and-filter units and air/air heat exchangers – SK 3120.200

Date : Jan 24, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Speed control For fan-and-filter units and air/air heat exchangers – SK 3120.200

created: 24.01.2019 build on www.rittal.com/uk-en



Product description

Description:	Temperature-dependent speed control to minimise noise and save energy in part-load operation.
Technical specifications:	For mounting on a 35 mm support rail EN 50 022 Phase cross-over with microcontroller Maximum fan output 300 W or 2 A
Supply includes:	Speed control NTC sensor, length 1.80 m
Note:	Only suitable for use with single-phase AC motors and equipment Not suitable for EC motors

Product features

Rated operating voltage:	100 V - 230 V
Dimensions:	Width: 105 mm Height: 90.5 mm Depth: 60.2 mm
Temperature range:	Setting range: +20°C...+55°C
Speed:	100 %
Packs of:	1 pc(s).
Weight/pack:	0.36 kg

EAN:	4028177631441
Customs tariff number:	90291000
ETIM 6.0:	EC000256
ETIM 5.0:	EC000256
eCl@ss 8.0/8.1:	27142320
eCl@ss 7.0/7.1:	27210707
eCl@ss 6.0/6.1:	27210707
eCl@ss 5.1/5.1.4:	27180792
Product description:	SK speed control unit , for filter fans and Air/air heat exchanger, 100 - 230 V, WHD: 105 x 90.5 x 60.2 mm
Approvals	
Approvals:	UR
Certificates:	EAC
Declarations:	Declaration of conformity