## Rittal - The System.

Faster – better – everywhere.

■ TopTherm air/air heat exchanger wall-mounted with controller – SK 3126.100

Date: Jan 24, 2019



## TopTherm air/air heat exchanger wall-mounted with controller – SK 3126.100

created: 24.01.2019 build on www.rittal.com/uk-en



Product description	
Colour:	RAL 7035
Protection category IP to IEC 60 529:	Internal circuit IP 54
Supply includes:	Complete unit ready for connection Plug-in terminal strip Floating fault signal contact in case of overtemperature
Product features	
Specific thermal output:	17.5 W/K
Air throughput (unimpeded air flow):	External circuit with 50 Hz: 265 m³/h External circuit with 60 Hz: 315 m³/h Internal circuit at 50 Hz: 265 m³/h Internal circuit at 60 Hz: 315 m³/h
Rated operating voltage:	230 V, 1~, 50 Hz/60 Hz
Dimensions:	Width: 280 mm Height: 550 mm Depth: 150 mm
Temperature control:	Electronic control with digital display (factory setting +35 °C)
Temperature range:	Operation (environment): -5°C+55°C
Power per fan:	At 50 Hz: 23 W

© Rittal 2019

Rated current (max.):	per fan at 50 Hz: 0.11 A per fan at 60 Hz: 0.13 A
Miniature circuit- breaker/fuse:	2 A
Packs of:	1 pc(s).
Weight/pack:	10 kg
EAN:	4028177388956
Customs tariff number:	84158300
ETIM 6.0:	EC002514
ETIM 5.0:	EC002514
eCl@ss 8.0/8.1:	27180711
eCl@ss 7.0/7.1:	27180711
eCl@ss 6.0/6.1:	27180711
eCl@ss 5.1/5.1.4:	27180711
Product description:	SK Air/Air heat exchanger TopTherm, wall-mounted with controller, 17.5 W/K, 230 V, 1~, 50/60 Hz, WHD: 280 x 550 x 150 mm
Approvals	
Approvals:	Approval overview UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity