

Rittal – The System.

Faster – better – everywhere.

► Utility lectern for TS, SE, CM, PC – PS 4638.600

Date : Jan 13, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Utility lectern for TS, SE, CM, PC – PS 4638.600

created: 13.01.2017 build on www.rittal.com/uk-en



Product description

Description: For programming units etc.; When required for servicing, it folds down quickly with a maximum support area, and after use is stowed between the tubular door frames in a space-saving design.

Material: Sheet steel

Colour: RAL 7035

Product features

To fit: Enclosure type: TS 8
Enclosure type: SE
Enclosure type: CM
Enclosure type: PC

Installation options: On the tubular door frame
For external mounting on surfaces.

To fit door width: 600 mm

Support area: Width: 413 mm
Depth: 400 mm

Load capacity: max. 30 kg.

Packs of: 1 pc(s).

Weight/pack: 3.8 kg

EAN:	4028177107496
Customs tariff number:	73269098
ETIM 6.0:	EC000784
ETIM 5.0:	EC000784
eCl@ss 8.0/8.1:	27180504
eCl@ss 7.0/7.1:	27182290
eCl@ss 6.0/6.1:	27182290
eCl@ss 5.1/5.1.4:	27189201

2017 © Rittal Ltd UK