

Rittal – The System.

Faster – better – everywhere.

► Slide rails, static installation for TS IT – DK 5501.450

Date : Jan 28, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Slide rails, static installation for TS IT – DK 5501.450

created: 28.01.2019 build on www.rittal.com/uk-en



Product description

Description:	Side system punchings for mounting accessories and cooling components that expel to the side.
Benefits:	Simply locate into the system punchings of the TS IT
Applications:	For mounting between the front and the rear pair of mounting angles To support heavy installed equipment
Material:	Sheet steel
Surface finish:	Zinc-plated
Supply includes:	Assembly parts
Note:	Effective contact surface 35 mm per side

Product features

Dimensions:	Length: 675 mm
Distance between levels:	745 mm
Contact surface:	Width: 35 mm
Units:	1 U
Load capacity:	80 kg, static load

Packs of:	2 pc(s).
Weight/pack:	2 kg
EAN:	4028177679009
Customs tariff number:	73269098
ETIM 6.0:	EC002620
ETIM 5.0:	EC002620
eCl@ss 8.0/8.1:	27189261
eCl@ss 7.0/7.1:	27182590
eCl@ss 6.0/6.1:	27182590
eCl@ss 5.1/5.1.4:	27182504
Product description:	DK Slide rail, 1 U, D: 675 mm, 80 kg, static, For two 482.6 mm (19") attachment level (front+rear), distance between levels:: 745 mm, static installation, for 482.6 mm (19") system punchings